

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW13 CLIMB TO 5000 DIRECT AQIMU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 314.75 INBOUND. CHART FAS OBST: 3507 ELEV 403045N/1013840W CHART FAS OBST: 3622 TOWER 403152N/1013957W CHART VDP AT 1.59 MILES TO RW13* *LNAV ONLY. WAAS CHANNEL # 66003 REFERENCE PATH ID: W13A DISTANCE TO THLD FROM 275 HAT: 0.74 NM							
HOLYO		HEXAP (FB)		060.73 / 13.92				5300									
HEXAP (IAF)		AXPUX (NOPT) (FB)		044.49 / 5.00				5100									
UYOGI (IAF)		AXPUX (NOPT) (FB)		230.86 / 5.09				5100									
AXPUX (IF/IAF)		JIKOS (FB)		134.55 / 6.18				5100									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NW AXPUX, RT, 134.55 INBOUND, 5100 FT. IN LIEU OF PT (IAF) 3. FAC: 134.60 FAF: JIKOS _____ DIST FAF TO MAP: 5.52 THLD: 5.52 4. MIN. ALT: AXPUX 5100, JIKOS 5100 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 5100 GS ALT AT: JIKOS _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 41.0 34:1 IS NOT CLEAR 8. MSA FROM: RW13 5100										MAG VAR: 9E		EPOCH YEAR: 2000					
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @					
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	3548	1	275	3548	1	275		NA			NA						
LNAV/VNAV DA	3752	1 3/4	479	3752	1 3/4	479		NA			NA						
LNAV MDA	3820	1	547	3820	1	547		NA			NA						
CIRCLING	3860	1	585	3860	1	585		NA			NA						
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -21C (-5F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. SEE 8260-10																	
CITY AND STATE				ELEVATION: 3275 TDZE: 3273				FACILITY IDENTIFIER:				PROCEDURE NO./AMDT NO.:				SUP:	
IMPERIAL, NE				AIRPORT NAME:				RNAV				RNAV (GPS) RWY 13, ORIG				AMDT: NONE	
				IMPERIAL MUNI								JUL - 5 2007				DATED	

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. -
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTES: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE OGALLALA ALTIMETER SETTING AND INCREASE ALL DAS 86 FEET AND ALL MDAS 100 FEET. VDP AND BARO-VNAV NA WHEN USING OGALLALA ALTIMETER SETTING.

CITY AND STATE

IMPERIAL, NE

ELEVATION: 3275 TDZE: 3273

AIRPORT NAME:

IMPERIAL MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 13, ORIG

JUL - 5 2007

SUP:

AMDT: NONE

DATED:

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. -
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTES: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE OGALLALA ALTIMETER SETTING AND INCREASE ALL DAS 86 FEET AND ALL MDAS 100 FEET. VDP AND BARO-VNAV NA WHEN USING OGALLALA ALTIMETER SETTING.

CITY AND STATE

IMPERIAL, NE

ELEVATION: 3275 TDZE: 3273

AIRPORT NAME:

IMPERIAL MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 13, ORIG

JUL - 5 2007

SUP:

AMDT: NONE

DATED:

**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KIML
RUNWAY	RW13
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W13A
LTP/FTP LATITUDE	403053.4360N
LTP/FTP LONGITUDE	1013733.1220W
LTP/FTP ELLIPSOIDAL HEIGHT	+09753
FPAP LATITUDE	402941.6200N
FPAP LONGITUDE	1013623.9000W
THRESHOLD CROSSING HEIGHT (TCH)	00041.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1216
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

43FB90E1

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+09975
FPAP ORTHOMETRIC HEIGHT	+09975

CITY AND STATE

IMPERIAL, NE

ELEVATION: 3275 TDZE: 3273

AIRPORT NAME:

IMPERIAL MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 13, ORIG

JUL - 5 2007

SUP:

AMDT:

NONE

DATED:

**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KIMLK3FR13	AHOLYO	010HOLYOK2EA0E	IF						18000		A JS	
SUSAP	KIMLK3FR13	AHOLYO	020HEXAPK3EA0E	A 020TF		06070139		+ 05300				A JS	
SUSAP	KIMLK3FR13	AHOLYO	030AXPUXK3EA0EE	L010TFY		04450050		+ 05100				A JS	
SUSAP	KIMLK3FR13	AUYOGI	010UYOGIK3EA0E	A IF						18000		A JS	
SUSAP	KIMLK3FR13	AUYOGI	020AXPUXK3EA0EE	010TF		23090051		+ 05100				A JS	
SUSAP	KIMLK3FR13	AAXPUX	010AXPUXK3EA0EE	CR HF		13460050		+ 05100		18000		A JS	
SUSAP	KIMLK3FR13	R	010AXPUXK3EA0E	I IF				+ 05100		18000		A JS	
SUSAP	KIMLK3FR13	R	020JIKOSK3EA0E	F 051TF		13460062		+ 05100			RW13	K3PGA	JS
SUSAP	KIMLK3FR13	R	030RW13	K3PGOGY M 031TF		13460055		03314		-300		A JS	
SUSAP	KIMLK3FR13	R	040AQIMUK3EA0EYM	010DF				+ 05000				A JS	
SUSAP	KIMLK3FR13	R	050AQIMUK3EA0EE	HR020HM		31480050		+ 05000				A JS	

[illegible][illegible]

CITY AND STATE
IMPERIAL, NE

ELEVATION: 3275 TDZE: 3273
AIRPORT NAME:
IMPERIAL MUNI

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:
RNAV (GPS) RWY 13, ORIG
JUL - 5 2007

SUP:	
AMDT:	NONE
DATED:	

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	