

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SVM VORTAC	ERNST INT/RADAR	041.00 / 19.77	2700

MAP: LOC: 3.29 NM AFTER ERNST INT/RADAR

CLIMBING LEFT TURN TO 3000 DIRECT SVM VORTAC AND HOLD.

ALTERNATE MA (DO NOT CHART): CLIMB TO 2700 ON HEADING 274.65 FOR RADAR VECTORS.

ADDITIONAL FLIGHT DATA:
 HOLD N, RT, 180.00 INBOUND.
 FAS OBST: 1189 AAO 424000N/0831959W.
 CHART 1269 TOWER 424034N/0831747W.
 CHART CIRCLING ICON.
 ERNST TO RW27L: 3.00/41.6.
 CHART (CFDST) AT 424019.30N/0831055.55W
 CHART IN PLANVIEW ONLY: SVM VORTAC 19.77 DME AT ERNST.

- PT R SIDE OF COURSE 094.65 OUTBOUND 2500 FT WITHIN 10 MILES OF ERNST (IAF)
-
- FAC 274.65 FAF ERNST INT/RADAR DIST FAF TO MAP 3.29 THLD 4.04
- MIN. ALT ERNST INT/RADAR 2300
- MSA FROM: KPTK 2900

MAG VAR: **7W** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			LOC: STANDARD@					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-LOC 27L	1440	1	466	1440	1	466	1440	1 3/8	466	1440	1 3/8	466			
CIRCLING	1500	1	519	1540	1	559	1640	1 3/4	659	1640	2	659			

NOTES:

CHART NOTE: CIRCLING RWY 09L, 36 NA AT NIGHT.

CHART PROFILE NOTE: DISREGARD GS INDICATIONS.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLEMAN A. YOUNG MUNI ALTIMETER SETTING AND INCREASE ALL MDA 120 FEET, INCREASE S-27L CAT C/D VISIBILITY 3/8 SM AND CIRCLING CAT C/D VISIBILITY 1/2 SM.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON SVM VORTAC AIRWAY RADIALS 085 CW 095.

@ NA WHEN TOWER CLOSED.
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE PONTIAC, MI	ELEVATION: 981 TDZE: 974 AIRPORT NAME: OAKLAND COUNTY INTL	FACILITY IDENTIFIER: I-PTK	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC BC RWY 27L, AMDT 2 19 JULY 2018	SUP AMDT 1 DATE 10/22/2009
--------------------------------------	---	--------------------------------------	--	--

**LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE PONTIAC, MI	ELEVATION: 981 TDZE: 974 AIRPORT NAME: OAKLAND COUNTY INTL	FACILITY IDENTIFIER: I-PTK	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: LOC BC RWY 27L, AMDT 2 19 JULY 2018	SUP:
				AMDT: 1
				DATED: 10/22/2009