

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
HUDON INT	AOO VOR	227.92 / 18.60	4100	MAP: 1.48 MILES AFTER AOO VOR CLIMB TO 3600 ON AOO VOR R-213 THEN CLIMBING RIGHT TURN TO 3900 DIRECT AOO VOR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 032.74 INBOUND. CHART FAS OBST: 1666 OL ON VOR 401932N/0781813W FAC CROSSES APPROACH END OF RWY 21

1. PT L SIDE OF COURSE 032.74 OUTBOUND 3900 FT WITHIN 10 MILES OF AOO VOR (IAF)
2. _____
3. FAC 212.74 FAF AOO VOR DIST FAF TO MAP 1.48 THLD _____
4. MIN. ALT AOO VOR 3000
8. MSA FROM: AOO VOR 360-180 4000, 180-360 4400

MAG VAR: TW EPOCH YEAR: 1965

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: NA	CIRCLING: STANDARD @						
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
CIRCLING	2420	1 1/4	917	2420	1 1/4	917	2420	2 3/4	917	2620	3	1117				

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEDFORD COUNTY ALTIMETER SETTING AND INCREASE CAT D MDA 100FT.

@ CAT A, B 1000-2, CAT C 1000-2 3/4, CAT D 1200-3
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
CHECKED

CITY AND STATE ALTOONA, PA	ELEVATION: 1503	TDZE:	FACILITY IDENTIFIER: AOO	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR-A, AMDT 5A 15 NOVEMBER 2012	SUP
	AIRPORT NAME:				AMDT 5
	ALTOONA-BLAIR COUNTY				DATE 05/10/2007