

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
INYOKERN	TWO	IYK2.LHS	ONE	07/24/2014	15 SEP 2016

TYPE: SID

DP ROUTE DESCRIPTION:

TAKEOFF RUNWAY 20: CLIMB TO 10000 ON HEADING 207.00 DEGREES AND LHS VORTAC R-015 TO LHS VORTAC, THEN PROCEED ON COURSE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes
-----------------	---------------------------	--------------------	---------------	--------	----------	-----	------	--------------------------

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: RADAR REQUIRED
TAKEOFF MINIMUMS:
RWY 2, 10, 15, 28, 33, NA – RESTRICTED AIRSPACE / TERRAIN.
RWY 20, STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 8200.

TAKEOFF OBSTACLES NOTES:

CONTROLLING OBSTACLES:

RWY 20: 3519 FT MSL AAO, 353627.02N/1175436.35.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: TOP ALTITUDE: 10000

QUALITY
15
CHECKED

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
INYOKERN	TWO	IYK2.LHS	ONE	07/24/2014	15 SEP 2016

AIRPORTS SERVED:

INYOKERN

INYOKERN, CA

COMMUNICATIONS:

HI-DESERT TRACON

FIXES AND/OR NAVAIDS:

KOLEE

REMARKS:

THE 400 FT CLIMB GRADIENT IS IN PLACE TO ENSURE THAT AIRCRAFT ARRIVE IN THE VICINITY OF KOLEE AT OR ABOVE 8200 TO ENSURE RECEPTION OF THE LHS VORTAC. THE HEADING OF 207 IS AIMED FROM THE END OF THE ICA TO KOLEE (MRA 8200). THERE IS NO POSITIVE COURSE GUIDANCE TO KOLEE, FIX IS GRAPHICALLY DISPLAYED ON PROCEDURE AT THE REQUEST OF ATC.

LISTED CONTROLLING OBSTACLE DRIVES 320 FT PER NM CLIMB GRADIENT

COORDINATED WITH: May 04, 2016

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
INYOKERN	TWO	IYK2.LHS	ONE	07/24/2014	15 SEP 2016

CHANGES:

ADDED CHART: TOP ALTITUDE: 10000

REASONS:

ATC REQUEST



DEPARTURE (DATA RECORD)

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
INYOKERN	TWO	IYK2 . LHS	ONE	07/24/2014	15 SEP 2016

ARINC SUMMARY - KIYK

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
RW20	010		VI	FB		207.0								
RW20	020	KOLEE	CF	FB		195.0	LHS							E
RW20	030	LHS	TF	FB								AA 10000		VE

POINTS

POINT NAME	LATITUDE	LONGITUDE
LHS	N344058.70	W1183436.98
KOLEE	N352744.66	W1180133.87

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION
RW20	N353944.30	W1174923.11	02416

QUALITY
15
CHECKED