U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.

Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated. Graphic depictions attached.

TYPE: RNAV SID

DP ROUTE DESCRIPTION:

TAKEOFF RWY 3: CLIMB TO 11000 DIRECT NARIC AND VIA 030.26 TRACK TO NILIY AND VIA 092.31 TRACK TO CHOIR, THENCE ... TAKEOFF RWY 13: CLIMB TO 11000 DIRECT RUCOR AND VIA 056.29 TRACK TO CHOIR, THENCE CLIMB IN HOLDING, (IF REQUIRED) BEFORE PROCEEDING ON COURSE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Computer F

From

Transition Name Codes FIX/NAVAID To FIX/NAVAID Course Distance MEA MOCA Crossing Altitudes/Fixes

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: GPS REQUIRED

NOTE: RNAV 1

TAKEOFF MINIMUMS:

RWY 21, NA- ATC RWY 31, NA- ATC

RWY 3, STANDARD WITH MINIMUM CLIMB OF 367 FEET PER NM TO 11000. RWY 13, STANDARD WITH MINIMUM CLIMB OF 389 FEET PER NM TO 11000.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 3, TREES, BUILDINGS, POLES AND A ROAD WITH VEHICLES BEGINNING 1' FROM DER, RIGHT AND LEFT OF CENTERLINE, UP TO 100' AGL/4659' MSL. NOTE: RWY 13, TREES AND ROAD WITH VEHICLES BEGINNING 1' FROM DER, RIGHT AND LEFT OF CENTERLINE, UP TO 100' AGL/4519' MSL.

CONTROLLING OBSTACLES:

RWY 3, 7399 MSL AAO 413129.77N/1201953.52W. RWY 13, 7399 MSL AAO 413129.77N/1201953.52W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KAAT 16E EPOCH YR 2005.
DME/DME SCREENING NOT CONDUCTED.
CHART HOLDING AT CHOIR: HOLD NW, LT,151.44 INBOUND.
CHART: TOP ALTITUDE: ASSIGNED BY ATC.

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.

Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number		Superseded Number	Dated	Effective Date 15 SEP 2016
CHOIR	THREE		TWO	04/10/2008	
AIRPORTS SERVED: ALTURAS MUNI		ALTURAS, CA			

COMMUNICATIONS:

SEATTLE CENTER, CTAF

FIXES AND/OR NAVAIDS:

REMARKS:

COORDINATED WITH: Apr 25, 2016

AOPA, NBAA, ZSE, AMGR

CHANGES:

ADDED CHART: TOP ALTITUDE: ASSIGNED BY ATC.

REASONS:

ATC REQUEST

OVALITY 15 CHECKED

DEPARTURE (DATA RECORD)

DP Name CHOIR		Number THREE		DP Computer Code CHOIR3.CHOIR		Superseded Number TWO		Dated 04/10/2008	Effective Date 15 SEP 2016	
										FIX/NAVAID
RWY 3 (AER)*	412851.48N/1203405.15W*	N	-	-	-	-			*DISPL THLD (240 FT)	
NARIC	413032.91N/1203144.23W	Υ	FB	DF	-	2.44			CG 367 FT/NM TO 11000	
NILIY	413441. 78N/1202557.66W	Υ	FB	TF	046.26	6.00				
CHOIR	413130.95N/1201313.20W	Υ	FB	TF	108.31	10.08				
RWY 13 (AER)*	412914.36N/1203409.86W*	N	-	-	-	-			*DISPL THLD (210) FT)
RUCOR	412657.75N/1203217.94W	Υ	FB	DF	-	2.67			CG 389 FT/NM TC	11000
CHOIR	413130.95N/1201313.20W	Υ	FB	TF	072.29	15.04				