

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
TTH VORTAC	HADBI (FB)	102.90 / 15.23	2500	LPV: DA LNAV/VNAV: DA LNAV: RW36 CLIMB TO 2500 DIRECT FAMTU AND HOLD.			
ZARHO	JANIX (FB)	263.11 / 14.40	2500				
HADBI (IAF)	EYUTA (NOPT) (FB)	094.04 / 5.00	2500	ADDITIONAL FLIGHT DATA: HOLD N, RT, 184.11 INBOUND. CHART FAS OBST: 899 TREE 393714N/0864901W CHART FAS OBST: 1130 TOWER 393500N/0864932W DISTANCE TO THLD FROM 294 HAT: 0.88 NM. CHART VDP AT 1.87 MILES TO RW36* *LNAV ONLY. WAAS CHANNEL # 40306 REFERENCE PATH ID: W36A			
JANIX (IAF)	EYUTA (NOPT) (FB)	274.18 / 5.00	2500				
EYUTA (IF/IAF)	AGUYU (FB)	004.11 / 6.18	2400				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)							
2. HOLD <u>S</u> EYUTA, RT, 004.11 INBOUND, 2500 FT. IN LIEU OF PT (IAF)							
3. FAC: <u>004.11</u> FAF: <u>AGUYU</u> DIST FAF TO MAP: <u>4.82</u> THLD: <u>4.82</u>							
4. MIN. ALT: <u>EYUTA 2500, AGUYU 2400</u>							
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>							
6. MIN GS INCPT: <u>2400</u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>							
7. GS ANGLE: <u>3.00</u> TCH: <u>30.0</u> 34:1 IS NOT CLEAR							
8. MSA FROM: <u>RW36 2600</u>							

MINIMUMS																
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X											
CATEGORY ==>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1123	1 1/4	294	1123	1 1/4	294		NA			NA					
LNAV/VNAV DA	1242	1 1/2	413	1242	1 1/2	413		NA			NA					
LNAV MDA	1440	1	611	1440	1	611		NA			NA					
CIRCLING	1440	1	598	1440	1	598		NA			NA					

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING INDIANAPOLIS INTL ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 SEE 8260-10

CITY AND STATE GREENCASTLE, IN	ELEVATION: 842 TDZE: 829	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 FEB 14 2008	SUP:
	AIRPORT NAME: PUTNAM COUNTY			AMDT: ORIG-A
	DATED 12/23/2004			

