

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE			LPV: DA LNAV/VNAV: DA LNAV: RW01 CLIMB TO 900 THEN CLIMBING RIGHT TURN TO 3500 DIRECT EKAKE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S EKAKE, RT, 012.44 INBOUND. CHART FAS OBST: 532 TOWER 431858N/0733717W DISTANCE TO THLD FROM 200 HAT: 0.47 NM. CHART VDP AT 1.33 NM TO RW01* *LNAV ONLY. WAAS CHANNEL # 87118 REFERENCE PATH ID: W01A CHART CIRCLING ICON. LTP HAE: 67.9 M									
EKAKE (IF/IAF)			CAGUG (FB)			012.44 / 6.01			2200												
CAGUG (FAF)			RW01 (MAP) (FO)			012.43 / 5.73															
RW01 (MAP)			900 MSL			012.43			900												
900 MSL			EKAKE (FO)						3500												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S EKAKE, RT, 012.44 INBOUND, 3500 FT. IN LIEU OF PT (IAF) 3. FAC: 012.43 FAF: CAGUG _____ DIST FAF TO MAP: 5.73 THLD: 5.73 4. MIN. ALT: EKAKE 3500, CAGUG 2200 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2200 GS ALT AT: CAGUG 2200 _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 53.3 34:1 IS CLEAR 8. MSA FROM: _____																		MAG VAR: 14W		EPOCH YEAR: 1980	
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
LPV DA	524	1/2	200	524	1/2	200	524	1/2	200	524	1/2	200									
LNAV/VNAV DA	835	1 1/4	511	835	1 1/4	511	835	1 1/4	511	835	1 1/4	511									
LNAV MDA	800	1/2	476	800	1/2	476	800	1	476	800	1	476									
CIRCLING	840	1	512	860	1	532	940	1 3/4	612	1960	3	1632									
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE ALBANY ALTIMETER SETTING AND INCREASE ALL DA 91 FEET AND ALL MDA 100 FEET; INCREASE LNAV/VNAV ALL CATS 3/8 SM, LNAV CAT C/D AND (CONTINUED ON PAGE 2)																					
CITY AND STATE GLENS FALLS, NY				ELEVATION: 328 TDZE: 324 AIRPORT NAME: FLOYD BENNETT MEMORIAL				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 2 5 JANUARY 2017				SUP:					
																AMDT: 1A					
																DATED 12/10/2015					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CIRCLING CAT C VISIBILITY 1/4 SM.

CHART NOTE: FOR INOPERATIVE ALS WHEN USING ALBANY ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 7/8 SM.

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING ALBANY ALTIMETER SETTING.

CHART NOTE: CIRCLING RWY 12, 30 NA AT NIGHT.

CHART NOTE: RWY 12, 30 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	282/30 CW 102/30 (NOPT)	282/7 CW 102/7	6200
2.	282/7 CW 102/7	EKAKE (IF/IAF) (FB)	3500
3.	102/30 CW 282/30	102/7 CW 282/7	6200
4.	102/7 CW 282/7	EKAKE (IF/IAF) (FB)	3500

QUALITY
16
CHECKED

CITY AND STATE GLENS FALLS, NY	ELEVATION: 328 AIRPORT NAME: FLOYD BENNETT MEMORIAL	TDZE: 324	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 2 5 JANUARY 2017	SUP:
					AMDT: 1A
					DATED: 12/10/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KGFL
RUNWAY	RW01
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01A
LTP/FTP LATITUDE	432008.4130N
LTP/FTP LONGITUDE	0733631.2445W
LTP/FTP ELLIPSOIDAL HEIGHT	+00679
FPAP LATITUDE	432137.4955N
FPAP LONGITUDE	0733634.5910W
THRESHOLD CROSSING HEIGHT (TCH)	00053.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1232
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

49A54BCB

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+00980
FPAP ORTHOMETRIC HEIGHT	+00980

QUALITY
16
CHECKED

CITY AND STATE

GLENS FALLS, NY

ELEVATION: 328

TDZE: 324

AIRPORT NAME:

FLOYD BENNETT MEMORIAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 1, AMDT 2

5 JANUARY 2017

SUP:

AMDT: 1A

DATED: 12/10/2015

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33												Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.																																																																																																																																													
ARINC SUMMARY - KGFL ROUTES <table style="width:100%; border-collapse: collapse; font-family: monospace; font-size: small;"> <thead> <tr> <th style="text-align: left;">TRANSITION</th> <th style="text-align: left;">WPT SEQ</th> <th style="text-align: left;">WPT NAME</th> <th style="text-align: left;">LEG TYPE</th> <th style="text-align: left;">FB/FO</th> <th style="text-align: left;">RNP</th> <th style="text-align: left;">MAG CRS</th> <th style="text-align: left;">REC NAV</th> <th style="text-align: left;">ANGLE</th> <th style="text-align: left;">TURN DIR</th> <th style="text-align: left;">CENTER FIX</th> <th style="text-align: left;">TURN RADIUS</th> <th style="text-align: left;">ALTITUDE DESCRIPTION & VALUE</th> <th style="text-align: left;">SPEED LIMIT DESCRIPTION & VALUE</th> <th style="text-align: left;">WPT DESCRIPTION CODE</th> </tr> </thead> <tbody> <tr> <td>EKAKE</td> <td>010</td> <td>EKAKE</td> <td>HF</td> <td>FO</td> <td></td> <td>012.4</td> <td></td> <td></td> <td>R</td> <td></td> <td></td> <td>AA 03500</td> <td></td> <td>EE A</td> </tr> <tr> <td></td> <td>010</td> <td>EKAKE</td> <td>IF</td> <td>FB</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 03500</td> <td></td> <td>E I</td> </tr> <tr> <td></td> <td>020</td> <td>CAGUG</td> <td>TF</td> <td>FB</td> <td>1.0</td> <td>012.4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 02200</td> <td></td> <td>E F</td> </tr> <tr> <td></td> <td>030</td> <td>RW01</td> <td>TF</td> <td>FO</td> <td>0.3</td> <td>012.4</td> <td></td> <td>3.00</td> <td></td> <td></td> <td></td> <td>AT 00375</td> <td></td> <td>GY M</td> </tr> <tr> <td></td> <td>040</td> <td></td> <td>CA</td> <td>FB</td> <td></td> <td>012.4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AA 00900</td> <td></td> <td>M</td> </tr> <tr> <td></td> <td>050</td> <td>EKAKE</td> <td>DF</td> <td>FO</td> <td>1.0</td> <td></td> <td></td> <td></td> <td>R</td> <td></td> <td></td> <td>AA 03500</td> <td></td> <td>EY</td> </tr> <tr> <td></td> <td>060</td> <td>EKAKE</td> <td>HM</td> <td>FO</td> <td></td> <td>012.4</td> <td></td> <td></td> <td>R</td> <td></td> <td></td> <td>AA 03500</td> <td></td> <td>EE</td> </tr> </tbody> </table> POINTS <table style="width:100%; border-collapse: collapse; font-family: monospace; font-size: small;"> <thead> <tr> <th style="text-align: left;">POINT NAME</th> <th style="text-align: left;">LATITUDE</th> <th style="text-align: left;">LONGITUDE</th> </tr> </thead> <tbody> <tr> <td>CAGUG</td> <td>N431424.59</td> <td>W0733618.36</td> </tr> <tr> <td>EKAKE</td> <td>N430824.13</td> <td>W0733604.89</td> </tr> </tbody> </table> RUNWAYS <table style="width:100%; border-collapse: collapse; font-family: monospace; font-size: small;"> <thead> <tr> <th style="text-align: left;">RUNWAY</th> <th style="text-align: left;">THRESHOLD LATITUDE</th> <th style="text-align: left;">THRESHOLD LONGITUDE</th> <th style="text-align: left;">THRESHOLD ELEVATION</th> <th style="text-align: left;">PROCEDURE TCH</th> </tr> </thead> <tbody> <tr> <td>RW01</td> <td>N432008.41</td> <td>W0733631.24</td> <td>00322</td> <td>53.4</td> </tr> </tbody> </table>															TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE	EKAKE	010	EKAKE	HF	FO		012.4			R			AA 03500		EE A		010	EKAKE	IF	FB								AA 03500		E I		020	CAGUG	TF	FB	1.0	012.4						AA 02200		E F		030	RW01	TF	FO	0.3	012.4		3.00				AT 00375		GY M		040		CA	FB		012.4						AA 00900		M		050	EKAKE	DF	FO	1.0				R			AA 03500		EY		060	EKAKE	HM	FO		012.4			R			AA 03500		EE	POINT NAME	LATITUDE	LONGITUDE	CAGUG	N431424.59	W0733618.36	EKAKE	N430824.13	W0733604.89	RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH	RW01	N432008.41	W0733631.24	00322	53.4
TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE																																																																																																																																											
EKAKE	010	EKAKE	HF	FO		012.4			R			AA 03500		EE A																																																																																																																																											
	010	EKAKE	IF	FB								AA 03500		E I																																																																																																																																											
	020	CAGUG	TF	FB	1.0	012.4						AA 02200		E F																																																																																																																																											
	030	RW01	TF	FO	0.3	012.4		3.00				AT 00375		GY M																																																																																																																																											
	040		CA	FB		012.4						AA 00900		M																																																																																																																																											
	050	EKAKE	DF	FO	1.0				R			AA 03500		EY																																																																																																																																											
	060	EKAKE	HM	FO		012.4			R			AA 03500		EE																																																																																																																																											
POINT NAME	LATITUDE	LONGITUDE																																																																																																																																																							
CAGUG	N431424.59	W0733618.36																																																																																																																																																							
EKAKE	N430824.13	W0733604.89																																																																																																																																																							
RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH																																																																																																																																																					
RW01	N432008.41	W0733631.24	00322	53.4																																																																																																																																																					
CITY AND STATE GLENS FALLS, NY		ELEVATION: 328 TDZE: 324 AIRPORT NAME: FLOYD BENNETT MEMORIAL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 2 5 JANUARY 2017			SUP: AMDT: 1A DATED: 12/10/2015																																																																																																																																																