

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SAVOONGA ALTIMETER SETTING AND INCREASE ALL DA 82 FT, INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, AND LNAV/VNAV ALL CATS VISIBILITY BY 1 MILE; INCREASE ALL MDA 100 FT AND LNAV VISIBILITY CAT B 1/4 MILE, CAT C AND D 1/2 MILE; INCREASE CIRCLING CATS B AND C 1/4 MILE.

CHART NOTE: FOR INOPERATIVE ODALS WHEN USING SAVOONGA ALTIMETER SETTING INCREASE LPV ALL CATS VISIBILITY 1/8 MILE.

CHART NOTE: FOR INOPERATIVE ODALS INCREASE LPV ALL CATS VISIBILITY 1/8 MILE.

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LNAV/VNAV ALL CATS, AND LNAV CATS C AND D.

CHART NOTE: WHEN USING SAVOONGA ALTIMETER SETTING INOPERATIVE TABLE DOES NOT APPLY TO LNAV/VNAV ALL CATS, AND LNAV CATS C AND D.

TAA

	FROM	TO	ALT
1.	254/30 CW 074/30 (NOPT)	254/6 CW 074/6	3300
	254/6 CW 074/6	JAYVE (IF/IAF) (FB)	3000
2.	074/30 CW 254/30	JAYVE (IF/IAF) (FO)	3000

QUALITY
6
CHECKED

CITY AND STATE GAMBELL, AK	ELEVATION: 29 THRE: 28 AIRPORT NAME: GAMBELL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 8 JANUARY 2015	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PAGM
RUNWAY	RW34
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W34A
LTP/FTP LATITUDE	634537.8775N
LTP/FTP LONGITUDE	1714351.1145W
LTP/FTP ELLIPSOIDAL HEIGHT	+00128
FPAP LATITUDE	634705.8400N
FPAP LONGITUDE	1714418.8500W
THRESHOLD CROSSING HEIGHT (TCH)	00038.7
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1376
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

5D830634

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PAGM
LTP ORTHOMETRIC HEIGHT	+00087
FPAP ORTHOMETRIC HEIGHT	+00087

QUALITY
6
CHECKED

CITY AND STATE GAMBELL, AK	ELEVATION: 29 THRE: 28 AIRPORT NAME: GAMBELL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 8 JANUARY 2015	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE GAMBELL, AK	ELEVATION: 29	THRE: 28	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: GAMBELL		RNAV	RNAV (GPS) RWY 34, ORIG	AMDT: NONE
				8 JANUARY 2015	DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	JAYVE	JAYVE	010	IAF	HF	R	FO		344.1(352.1T)	004.0	AA 03000	
		JAYVE	010	FACF	IF		FB				AA 03000	
		KALIX	020	FAF	TF		FB	0.5	344.1(352.1T)	007.0	AA 01700	
		RW34	030	MAP	TF		FO	0.3	344.1(352.1T)	005.1	AT 00067	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		344.1(352.1T)		AA 00278	
	PEZUM	050		DF		FO				AA 03000	
	PEZUM	060		HM	R	FO		164.0(172.0T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	JAYVE	N633339.28	W1714006.32	N6333.655	W17140.105
	KALIX	N634034.13	W1714215.70	N6340.569	W17142.262
	PEZUM	N635820.22	W1714753.01	N6358.337	W17147.884
	RW34	N634537.88	W1714351.11	N6345.631	W17143.852

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW34	00028	39

QUALITY
6
CHECKED

CITY AND STATE GAMBELL, AK	ELEVATION: 29	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 8 JANUARY 2015	SUP:
	AIRPORT NAME: GAMBELL			AMDT: NONE
				DATED: