U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVB unless otherwise indicated.

nautical miles. Visibilities are in statute miles or feet RVR unless otherwis	e indicated.			
(1) TAKEOFF MINIMUMS:				
RWY 12, STANDARD RWY 30, 300-2 OR STANDARD WITH MINIMUM (RWY 18, 36 NA - ENVIRONMENTAL	CLIMB OF 239 FT PER NM TO 700.			
(2) TEXTUAL DEPARTURE PROCEDURE:				
(2) TAKEOFE OPETAGLE NOTES.				
(3) TAKEOFF OBSTACLE NOTES:				
NOTE: RWY 30, TOWER 1.5 NM FROM DER, 2566' RIGHT OF CENTERLINE, 230' AGL / 542' MSL.				
(4) CONTROLLING OBSTACLES:				
(5) City, State BEEVILLE, TX	(6) Airport BEEVILLE MUNI	(7) Effective Date JUL - 5		(8) Amdt. No. ORIG