

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
DANVILLE, VA	DANVILLE RGNL	24 JULY 2014	2

**TAKEOFF MINIMUMS:**

RWY 02, 20, 31: STANDARD

RWY 13: 300-1 1/4 OR STANDARD WITH MINIMUM CLIMB OF 232 FT PER NM TO 800.

**TEXTUAL DEPARTURE PROCEDURES:**

**TAKEOFF OBSTACLE NOTES:**

NOTE RWY 02: TREES BEGINNING 285 FEET FROM DER, 455 FEET RIGHT OF CENTERLINE, UP TO 22 FEET AGL/587 FEET MSL.

NOTE RWY 20: TREE 1328 FEET FROM DER, 633 FEET RIGHT OF CENTERLINE, 30 FEET AGL/569 FEET MSL.

NOTE RWY 13: TREES BEGINNING 189 FEET FROM DER, 90 FEET RIGHT OF CENTERLINE, UP TO 100 FEET AGL/711 FEET MSL.

BUILDING 1310 FEET FROM DER, 194 FEET RIGHT OF CENTERLINE, 10 FEET AGL/562 FEET MSL. POLE 1496 FEET FROM DER, 277 FEET RIGHT OF CENTERLINE, 29 FEET AGL/590 FEET MSL. TREES BEGINNING AT DER, 8 FEET LEFT OF CENTERLINE, UP TO 74 FEET AGL/613 FEET MSL.

NOTE RWY 31: TREES BEGINNING 823 FEET FROM DER, 6 FEET LEFT OF CENTERLINE, UP TO 85 FEET AGL/699 FEET MSL. POLE 1185 FEET FROM DER, 253 FEET LEFT OF CENTERLINE, 30 FEET AGL/608 FEET MSL. POLE 2056 FEET FROM DER, 253 FEET LEFT OF CENTERLINE, 38 FEET AGL/626 FEET MSL. SIGN 2196 FEET FROM DER, 328 FEET LEFT OF CENTERLINE, 36 FEET AGL/628 FEET MSL. TOWER 1165 FEET FROM DER, 416 FEET LEFT OF CENTERLINE, 64 FEET AGL / 641 FEET MSL. BUILDING 568 FEET FROM DER, 455 FEET LEFT OF CENTERLINE, 37 FEET AGL/612 FEET MSL. BUILDING 395 FEET FROM DER, 573 FEET LEFT OF CENTERLINE, 28 FEET AGL/602 FEET MSL. TREES BEGINNING 1358 FEET FROM DER, 24 FEET RIGHT OF CENTERLINE, UP TO 73 FEET AGL / 700 FEET MSL. POLE 1540 FEET FROM DER, 111 FEET RIGHT OF CENTERLINE, 44 FEET AGL/613 FEET MSL. POLE 1365 FEET FROM DER, 131 FEET RIGHT OF CENTERLINE, 32 FEET AGL/606 FEET MSL. POLE 3042 FEET FROM DER, 174 FEET RIGHT OF CENTERLINE, 75 FEET AGL/681 FEET MSL. POLE 2897 FEET FROM DER, 284 FEET RIGHT OF CENTERLINE, 75 FEET AGL/682 FEET MSL. BUILDING 2308 FEET FROM DER, 584 FEET RIGHT OF CENTERLINE, 40 FEET AGL/647 FEET MSL.

**CONTROLLING OBSTACLES:**

RWY 13: 711 MSL TREE, 363329.20N/0791848.57W



U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
DANVILLE, VA	DANVILLE RGNL	24 JULY 2014	2

**REMARKS:**

**FLIGHT INSPECTED BY:**

Joel F Hawkley  5/22/14

**REQUIRED EFFECTIVE DATE:**

ROUTINE

**DEVELOPED BY:**

PATRICK MULQUEEN   
(DAVID TEFFETELLER) AIV-351

08/19/2013

**APPROVED BY:**

STEVEN SZUKALA  AUV-351

JUN 04 2014

**COORDINATED WITH:**

ALPA, AOPA, NBAA, ZDC, ARPT MNGR

**CHANGES:**

1. UPDATED TAKEOFF MINS FOR RWY 13: CHANGED MINIMUM CLIMB 299 TO 900 TO 232 TO 800.
2. UPDATED TAKEOFF OBSTACLE NOTES FOR RWY 02, 20, 13, AND 31.

**REASONS:**

- 1, 2. 8260.46D FORMATTING / UPDATED AIRPORT AND OBSTACLE SURVEYS

