

U.S. Department of Transportation
Federal Aviation Administration

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
LOZ VORTAC ESONE INT / I-LOZ 12.55 DME (IAF)	ADUPY INT / I-LOZ 6.35 DME	266.47 / 3.07	4000	ILS: AT THE DH. LOC: 5.38 MILES AFTER
	ADUPY (NoPT)	057.30 / 6.19 (I-LOZ)	3000	ADUPY OR AT I-LOZ 0.98 DME FIX
	CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 4000 DIRECT LOZ VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000.			
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 245.88 INBOUND. CHART FAS OBST: 1439 TREE 370233N / 0840824W

1. PT R SIDE OF COURSE 237.30 OUTBOUND 3500 FT WITHIN 10 MILES OF ADUPY (IAF)
2.
3. FAC: 057.30 FAF: ADUPY DIST FAF TO MAP: 5.38 THLD: 5.38
4. MIN. ALT: ADUPY 3000
5. DIST TO THLD FROM OM: 5.38 MM: IM: 150 HAT: 100 HAT: GS ANT: 1089
6. MIN GS INCPT: 3000 GS ALT AT: ADUPY 3000 OM: - MM: - IM: -
7. GS ANGLE: 3.00 TCH: 48.8
8. MSA FROM: LOZ VORTAC 090-200 4400, 200-090 3400

CHART VDP AT 2.35 DME;
DISTANCE VDP TO THLD 1.37 MILES.

MAG VAR: 5W EPOCH YEAR: 05

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM	8260-15A	FOR THIS AIRPORT	ALTERNATE: N A		ILS: STANDARD# @	LOC: STANDARD## @						
CATEGORY ==>		A			B			C			D			E		
		DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
S-ILS 6		1412	3/4	200	1412	3/4	200	1412	3/4	200	1412	3/4	200			
S-LOC 6		1700	1	488	1700	1	488	1700	1 1/4	488	1700	1 1/2	488			
CIRCLING		1780	1	568	1780	1	568	2040	2 1/2	828	2040	2 3/4	828			

NOTES:

CHART NOTES: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE SOMERSET ALTIMETER SETTING AND INCREASE ALL DAs/ MDAs 100 FEET. VDP NA WHEN USING SOMERSET ALTIMETER SETTING.

ILS: CAT C 900-2 1/2, CAT D 900-2 3/4.
LOC: CAT C 900-2 1/2, CAT D 900-2 3/4
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE LONDON, KY	ELEVATION: 1212 TDZE: 1212	FACILITY IDENTIFIER: I-LOZ	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: SEP 28 2006 ILS OR LOC RWY 6, AMDT 1	SUP:
	AIRPORT NAME: LONDON-CORBIN ARPT-MAGEE FLD			AMDT: ORIG
	DATE: 10/27/05			

