

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
UNAWO (IF/IAF)	XIRNY (FB)	354.28 / 5.00	1800	LNAV: RW35 CLIMB TO 2500 DIRECT ZEREL AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 174.34 INBOUND. FAS OBST: 253 AAO 605200N/1623224W XIRNY TO RW35: 3.00/40. CHART BETHEL AWOS-3.			
XIRNY (FAF)	RW35 (MAP) (FO)	354.29 / 5.38					
RW35 (MAP)	448 MSL	354.29					
448 MSL	ZEREL (FO)		2500				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)	
2. HOLD S UNAWO, RT, 354.28 INBOUND, 2600 FT. IN LIEU OF PT (IAF)	
3. FAC: <u>354.29</u> FAF: <u>XIRNY</u> DIST FAF TO MAP: <u>5.38</u> THLD: <u>5.38</u>	
4. MIN. ALT: <u>UNAWO 2600, XIRNY 1800</u>	
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCP: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS CLEAR	
8. MSA FROM: <u> </u>	

MAG VAR: 12E EPOCH YEAR: 2015

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT												ALTERNATE: N A X			
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	680	1	632	680	1	632		NA			NA				
CIRCLING	720	1	672	720	1	672		NA			NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: USE BETHEL ALTIMETER SETTING, WHEN NOT RECEIVED, PROCEDURE NA.

CITY AND STATE KASIGLUK, AK	ELEVATION: 48 THRE: 48	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 22 AUGUST 2013	SUP:
	AIRPORT NAME: KASIGLUK			AMDT: NONE
				DATED

QUALITY
5
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	264/30 CW 084/30 (NOPT)	UNAWO (IF/IAF) (FB)	2600
2.	084/30 CW 264/30	UNAWO (IF/IAF) (FO)	2600

QUALITY
CHECKED

CITY AND STATE
KASIGLUK, AK

ELEVATION: 48 THRE: 48
AIRPORT NAME:
KASIGLUK

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 35, ORIG
22 AUGUST 2013

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE KASIGLUK, AK	ELEVATION: 48	THRE: 48	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 35, ORIG	AMDT: NONE
	KASIGLUK		RNAV	22 AUGUST 2013	DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	UNAWO	UNAWO	010	IAF	HF	R	FO		354.3(006.3T)	004.0	AA 02600	
		UNAWO	010	FACF	IF		FB				AA 02600	
		XIRNY	020	FAF	TF		FB	0.5	354.3(006.3T)	005.0	AA 01800	
		RW35	030	MAP	TF		FO	0.3	354.3(006.3T)	005.4	AT 00088	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		354.3(006.3T)		AA 00448	
	ZEREL	050		DF		FO				AA 02500	
	ZEREL	060		HM	R	FO		174.3(186.3T)	004.0	AA 02500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	UNAWO	N604152.00	W1623350.07	N6041.867	W16233.835
	XIRNY	N604649.56	W1623243.13	N6046.826	W16232.719
	ZEREL	N610240.55	W1622906.90	N6102.676	W16229.115
	RW35	N605209.35	W1623130.81	N6052.156	W16231.514

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00048	40

CITY AND STATE
KASIGLUK, AK

ELEVATION: 48
AIRPORT NAME: KASIGLUK
THRE: 48

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 35, ORIG
22 AUGUST 2013

SUP:
AMDT: NONE
DATED: