

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**LOC STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: LOC: GECEK/I-LRD 0.48 DME
HEVUM/LRD 10.00 DME CW (IAF)	FOMUX/I-LRD 12.66 DME	10.00 DME ARC (LRD LR-177)	3000	CLIMB TO 1100 THEN CLIMBING LEFT TURN TO 2600 ON HEADING 290 AND ON LRD VORTAC R-319 TO BLAME/LRD 18.00 DME AND HOLD.
FOMUX/I-LRD 12.66 DME (IF)	TITTO/I-LRD 5.73 DME	357.55 / 6.93 (I-LRD)	2400	
				ADDITIONAL FLIGHT DATA: HOLD NW, LT, 139.26 INBOUND. CHART FAS OBST: 562 POLE 273011N/0992809W. CHART 668 TOWER 272943N/0992816W. CHART LRD R-132 AT HEVUM. CHART CIRCLING ICON. TITTO TO RW36L: 3.00/50. CHART PLANVIEW NOTE: DME REQUIRED.

- PT \_\_\_\_\_ SIDE OF COURSE \_\_\_\_\_ OUTBOUND \_\_\_\_\_ FT WITHIN \_\_\_\_\_ MILES OF \_\_\_\_\_ (IAF)
- PROFILE STARTS AT FOMUX
- FAC 357.55 FAF TITTO/I-LRD 5.73 DME DIST FAF TO MAP \_\_\_\_\_ THLD 5.85
- MIN. ALT FOMUX 3000, TITTO 2400, ERXIW/I-LRD 1.68 DME 1100
- MSA FROM: LRD VORTAC 2600

MAG VAR: 5E EPOCH YEAR: 2020

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-LOC 36L	820	1	323	820	1	323	820	1	323	820	1	323	820	1	323
CIRCLING	940	1	432	980	1	472	1100	1 1/2	592	1200	2 1/4	692	1200	2 1/2	692

NOTES:  
 CHART NOTE: CIRCLING NA W OF RWYS 14 AND 36L.  
 CHART NOTE: DME REQUIRED.  
 CHART PROFILE NOTE: USE I-LRD DME WHEN ON THE LOCALIZER COURSE.  
 CHART PROFILE NOTE: DISREGARD GS INDICATIONS.

@ NA WHEN CONTROL TOWER CLOSED.  
 @ CAT D 800-2 1/4, CAT E 800-2 1/2



CITY AND STATE LAREDO, TX	ELEVATION: 508 TDZE: 497 AIRPORT NAME: LAREDO INTL	FACILITY IDENTIFIER: I-LRD	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC BC RWY 36L, AMDT 3 1 FEBRUARY 2018	SUP LOC/DME BC RWY 35L AMDT 2 DATE 08/30/2007
------------------------------	--	-------------------------------	---	--

**LOC STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE <b>LAREDO, TX</b>	<b>ELEVATION: 508</b>	<b>TDZE: 497</b>	FACILITY IDENTIFIER: <b>I-LRD</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>LOC BC RWY 36L, AMDT 3</b> 1 FEBRUARY 2018	SUP: <b>LOC/DME BC RWY 35L</b>
	AIRPORT NAME: <b>LAREDO INTL</b>				AMDT: <b>2</b>
					DATED: <b>08/30/2007</b>