

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
ORLANDO, FL	ORLANDO INTL	7 DECEMBER 2017	3A

TAKEOFF MINIMUMS:
STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

VISUAL CLIMB OVER AIRPORT:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 17L: NAVAID 9 FT FROM DER, ON CENTERLINE, 1 FT AGL/90 FT MSL. LIGHT POLE 9 FT FROM DER, 120 FT LEFT OF CENTERLINE, 3 FT AGL/91 FT MSL. TREE 1534 FT FROM DER, 902 FT LEFT OF CENTERLINE, 74 FT AGL/152 FT MSL.

NOTE: RWY 17R: TREE 1373 FT FROM DER, 855 FT RIGHT OF CENTERLINE, 58 FT AGL/133 FT MSL. TREES BEGINNING 1473 FT FROM DER, 873 FT RIGHT OF CENTERLINE, UP TO 60 FT AGL/136 FT MSL.

NOTE: RWY 18L: LIGHT POLE 13 FT FROM DER, 283 FT RIGHT OF CENTERLINE, 3 FT AGL/94 FT MSL. TREE 2863 FT FROM DER, 1079 FT LEFT OF CENTERLINE, 89 FT AGL/169 FT MSL. TREES BEGINNING 2930 FT FROM DER, 1166 FT LEFT OF CENTERLINE, UP TO 95 FT AGL/171 FT MSL.

NOTE: RWY 18R: LIGHT POLE 14 FT FROM DER, 282 FT LEFT OF CENTERLINE, 3 FT AGL/92 FT MSL.

NOTE: RWY 35L: LIGHT POLE 15 FT FROM DER, 283 FT RIGHT OF CENTERLINE, 5 FT AGL/92 FT MSL. POLE 1250 FT FROM DER, 686 FT LEFT OF CENTERLINE, 45 FT AGL/129 FT MSL.

NOTE: RWY 35R: NAVAID 9 FT FROM DER, ON CENTERLINE, 1 FT AGL/90 FT MSL. NAVAID 1191 FT FROM DER, 768 FT RIGHT OF CENTERLINE, 36 FT AGL/125 FT MSL. POLE 1661 FT FROM DER, 922 FT RIGHT OF CENTERLINE, 44 FT AGL/133 FT MSL. POLE 1712 FT FROM DER, 916 FT LEFT OF CENTERLINE, 25 FT AGL/134 FT MSL. TREES BEGINNING 2235 FT FROM DER, 1012 FT RIGHT OF CENTERLINE, UP TO 167 FT MSL.

NOTE: RWY 36L: SIGN 3 FT FROM DER, 373 FT LEFT OF CENTERLINE, 3 FT AGL/93 FT MSL. POLE 1061 FT FROM DER, 779 FT LEFT OF CENTERLINE, 45 FT AGL/137 FT MSL. SIGN 1063 FT FROM DER, 775 FT RIGHT OF CENTERLINE, 38 FT AGL/123 FT MSL.

NOTE: RWY 36R: BUILDING AND TREE BEGINNING 962 FT FROM DER, 582 FT RIGHT OF CENTERLINE, UP TO 30 FT AGL/121 FT MSL. SIGN 1054 FT FROM DER, 704 FT LEFT OF CENTERLINE, 29 FT AGL/119 FT MSL. SIGN 1062 FT FROM DER, 725 FT LEFT OF CENTERLINE, 38 FT AGL/123 FT MSL.

CONTROLLING OBSTACLES:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
ORLANDO, FL	ORLANDO INTL	7 DECEMBER 2017	3A

REMARKS:

<u>FLIGHT INSPECTED BY:</u>	<i>Digitally signed by</i> ROBERT G HAMILTON Aug 03, 2017	<u>OFFICE SYMBOL:</u>	<u>DATE:</u>
MIRC J HINCK		FICO	7/31/17
<u>DEVELOPED BY:</u>	<i>Digitally signed by</i> PETER R GUIMOND Jun 09, 2017	<u>OFFICE SYMBOL:</u>	<u>DATE:</u>
PETER GUIMOND		AJV-5422	06/09/2017
<u>APPROVED BY:</u>	<i>Digitally signed by</i> STEVEN A VARGAS Jul 06, 2017	<u>OFFICE SYMBOL:</u>	<u>DATE:</u>
JULIE MORGAN		AJV-5420	

REQUIRED EFFECTIVE DATE:
ROUTINE

COORDINATED WITH:

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
☒	☒	☒	☒	☐	☒

OTHER:
ZJX, ORL APP CON, ORL ATCT, AMGR

CHANGES - REASONS:

AMENDED TAKEOFF OBSTACLE NOTES FOR RWY 17L, 17R, 18L, 35L, 35R, 36L, AND 36R - NEW OBSTACLE STUDY. GROUPED AND FORMATTED IN ACCORDANCE WITH DEPARTURE OBSTACLES GROUPER (1.0) STANDARD OPERATING PROCEDURE.

QUALITY
3
CHECKED