### FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE **GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAM GROMO						<u>NUMBER</u> FOUR	DP COMPUTER CODE GROMO4.GROMO	SUPERSEDED NUMBER THREE	<b>DATED</b> 7/26/2012	EFFECTIVE DATE
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV					10 NOV 2016
			$\boxtimes$							
				THIS IS	A CORR	ECTED COPY (	OF A PROCEDURE	PREVIOUSLY PUBL	ISHED IN N	IEDD'S 167 & 181

#### **DP ROUTE DESCRIPTION:**

TAKEOFF RWY 9, 27: CLIMBING LEFT TURN THENCE...

TAKEOFF RWY 22: CLIMBING RIGHT TURN THENCE...

...INTERCEPT AND PROCEED ON YKM VORTAC R-250 TO GROMO/YKM 9.00 DME, THEN ON ASSIGNED TRANSITION.

#### TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	TRANSITION COMPUTER CODE	<u>FROM</u> <u>FIX/NAVAID</u>	<u>TO</u> <u>FIX/NAVAID</u>	<u>COURSE</u>	DISTANCE	<u>MEA</u>	MOCA	CROSSING ALTITUDE/FIXES
TAMPO	GROMO4.TAMPO	GROMO/YKM 9.00 DME	TAMPO INT/YKM 17.42 DME	250.00 (YKM R-250)	8.42	8000		
SIMCO	GROMO4.SIMCO	GROMO/YKM 9.00 DME	OGFAW INT/YKM 9.00 DME	YKM 9.00 DME ARC CCW				
			SIMCO INT/YKM 19.89 DME	220.91 (YKM R-221)	10.89	12000		
HITCH	GROMO4.HITCH	GROMO/YKM 9.00 DME	OGXOB/YKM 9.00 DME	YKM 9.00 DME ARC CCW				
			HITCH INT/YKM 16.00 DME	206.00 (YKM R-206)	7.00	8000		
GUBSE	GROMO4.GUBSE	GROMO/YKM 9.00 DME	OGZOF/YKM 9.00 DME	YKM 9.00 DME ARC CCW				
			GUBSE INT/YKM 16.00 DME	187.27 (YKM R-187)	7.00	7800		
PAPPS	GROMO4.PAPPS	GROMO/YKM 9.00 DME	OHKAR/YKM 9.00 DME	YKM 9.00 DME ARC CCW				
			PAPPS INT/YKM 25.45 DME	087.00 (YKM R-087) YKM	16.45	6000		
SUNED	GROMO4.SUNED	GROMO/YKM 9.00 DME	OHAWY/YKM 9.00 DME	YKM 9.00 DME ARC CCW				
			SUNED INT/YKM 26.03 DME	108.24 (YKM R-108)	17.03	6000		

#### **PROCEDURAL DATA NOTES:**

CHART NOTE: DME REQUIRED.

CHART NOTE: TAMPO TRANSITION REQUIRED MINIMUM CLIMB TO 8100.

NOTE: TAMPO TRANSITION: CLIMB IN HOLD E, RT, 250.00 INBOUND TO 8100 BEFORE PROCEEDING ON COURSE. NOTE: SIMCO TRANSITION: CLIMB IN HOLD NE, RT, 221.00 INBOUND TO 12000 BEFORE PROCEEDING ON COURSE. NOTE: HITCH TRANSITION: CLIMB IN HOLD, NE, RT, 206.00 INBOUND TO 8000 BEFORE PROCEEDING ON COURSE.

### **TAKEOFF MINIMUMS:**

**RWY 4. NA- OBSTACLES** 

RWY 9- STANDARD WITH MINIMUM CLIMB OF 405 FT PER NM TO 6300.

RWY 22- STANDARD WITH MINIMUM CLIMB OF 380 FT PER NM TO 6300.

RWY 27- STANDARD WITH MINIMUM CLIMB OF 380 FT PER NM TO 6300.

## FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAMENUMBERDP COMPUTER CODESUPERSEDED NUMBERDATEDEFFECTIVE DATEGROMOFOURGROMO4.GROMOTHREE7/26/201210 NOV 2016

#### **TAKEOFF OBSTACLES NOTES:**

NOTE: RWY 9, OL ON BLDG 27 FT FROM DER, 507 FT RIGHT OF CENTERLINE, 34 FT AGL/1074 FT MSL. POLE 388 FT FROM DER, 561 FT RIGHT OF CENTERLINE, 34 FT AGL/1073 FT MSL. TREES BEGINNING 586 FT FROM DER. 550 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/1139 FT MSL.

NOTE: RWY 22, FENCE BEGINNING 27 FT FROM DER, 435 FT RIGHT OF CENTERLINE, UP TO 10 FT AGL/1085 FT MSL. TREES BEGINNING 570 FT FROM DER, 228 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/1199 FT MSL. TREES BEGINNING 3195 FT FROM DER, 202 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/1199 FT MSL. TREES BEGINNING 1.0 NM FROM DER, 732 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/1239 FT MSL.

NOTE: RWY 27, ANT ON BLDG 398 FT FROM DER, 282 FT LEFT OF CENTERLINE, 15 FT AGL/1117 FT MSL. TREES BEGINNING 3824 FT FROM DER, 1341 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/1239 FT MSL.

#### **CONTROLLING OBSTACLES:**

RWY 9: 3302 FT MSL TOWER 463825.00N/1202349.00W, 6720 FT MSL AAO 463439.00N/1210636.00W.

RWY 22: 6720 FT MSL AAO 463439.00N/1210636.00W, 2698 FT MSL AAO 463059.09N/1203533.44W.

RWY 27: 6720 FT MSL AAO 463439.00N/1210636.00W, 2698 FT MSL AAO 463059.09N/1203533.44W.

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 9, 22, 27 - 12476 FT MSL AAO 461218.90N/1212915.40W.

#### LOST COMMUNICATIONS PROCEDURES:

#### **ADDITIONAL FLIGHT DATA:**

CHART: R-6714A, B, C, D.

CHART HOLDING AT TAMPO INT/YKM 17.42 DME, E, RT, 250.00 INBOUND.

CHART HOLDING AT HITCH INT/YKM 16 DME, NE, RT, 206.00 INBOUND.

CHART HOLDING AT SIMCO INT/YKM 19.89 DME NE, RT, 221.00 INBOUND.

CHART: V204, GROMO-TAMPO, V448, OGFAW-SIMCO, V468, OGXOB-HITCH, V25, OGZOF-GUBSE, V4-298, OHAWY-SUNED, V204, OHKAR-PAPPS.

#### **AIRPORTS SERVED:**

AIRPORT NAME	CITY	STATE
YAKIMA AIR TERMINAL/MCALLISTER FIELD	YAKIMA	WA

#### **COMMUNICATIONS:**

ATIS. CLNC DEL. YAKIMA GROUND CONTROL. YKM ATCT. CHINOOK APP CON.

#### **FIXES AND/OR NAVAIDS:**

YKM VORTAC, ELN VOR/DME, LTJ VOR/DME

#### REMARKS:

FLIGHT CHECK 4D ACCURACY REQUESTED FOR 3302 FT MSL TOWER 463825.00N/1202349.00W. GROMO FOUR AMENDMENT DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS.

# FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<b>DP COMPUTER CODE</b>	SUPERSEDED NUMBER	DATED	<b>EFFECTIVE DATE</b>
GROMO	FOUR	GROMO4.GROMO	THREE	7/26/2012	10 NOV 2016

COORDINATED WIT	п	ľ
-----------------	---	---

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	NBAA
	$\boxtimes$	$\boxtimes$			$\boxtimes$

#### OTHER:

ZSE, APRT MGR, YKM ATCT, CHINOOK APP CON.

### **CHANGES - REASONS:**

- 1. CHANGED ELN VORTAC TO ELN VOR/DME.- TACAN ANTENNA REPLACED WITH DME.
- 2. ADDED REMARK "GROMO FOUR AMENDMENT DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS"- A MINOR AMENDMENT DOES NOT QUALIFY AS A PERIODIC REVIEW.

9/11/2016: THIS IS A CORRCTED COPY OF THE FORM PROCESSED ON 7/08/2016. ADDED LAST FLIGHT INSPECTION DATE.

10/3/20146: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON08/03/2016, CHANGED LTJ VORTAC TO LTJ VOR/DME.