

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES											MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LNAV: RW19 CLIMB TO 2000 DIRECT HEGOG AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 014.84 INBOUND. CHART FAS OBST: 231 TREE 332119N/0911917W WUDAP TO RW19: 3.00/40. CHART CIRCLING ICON. CHART GREENVILLE ASOS.						
OZIGE (IF/IAF)		WUDAP (FB)			194.91 / 6.66			1700								
WUDAP (FAF)		SKEPS/2.60 NM TO RW19 (FB)			194.89 / 2.22											
SKEPS/2.60 NM TO RW19		RW19 (MAP) (FO)			194.89 / 2.60											
RW19 (MAP)		526 MSL			194.89			2000								
526 MSL		HEGOG (FO)														
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N OZIGE, RT, 194.91 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>194.89</u> FAF: <u>WUDAP</u> DIST FAF TO MAP: <u>4.82</u> THLD: <u>4.82</u> 4. MIN. ALT: OZIGE 2000, WUDAP 1700, SKEPS/2.60 NM TO RW19 980 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____																
											MAG VAR: 1W		EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A ☒ X									
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	540	1	415	540	1	415	540	1 1/8	415	540	1 1/8	415				
CIRCLING	620	1	494	720	1	594	720	1 1/2	594	720	2	594				
NOTES: CHART NOTE: CIRCLING NA EAST OF RWY 1-19. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 126 TDZE: 125			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP: 4				
LAKE VILLAGE, AR		AIRPORT NAME:			LAKE VILLAGE MUNI		RNAV (GPS) RWY 19, AMDT 1					AMDT: ORIG-B				
							2 MARCH 2017					DATED 09/17/2015				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: USE GREENVILLE ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	105/30 CW 285/30 (NOPT)	105/15 CW 285/15	2100
	105/15 CW 285/15 (NOPT)	OZIGE (IF/IAF) (FB)	2000
2.	285/30 CW 105/30	OZIGE (IAF) (FO)	2000

CITY AND STATE

LAKE VILLAGE, AR

ELEVATION: 126

TDZE: 125

AIRPORT NAME:

LAKE VILLAGE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 19, AMDT 1

2 MARCH 2017

SUP:

4

AMDT: ORG-B

DATED: 09/17/2015

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - M32

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
OZIGE	010	OZIGE	HF	FO		194.9			R			AA 02000		EE A
	010	OZIGE	IF	FB								AA 02000		E I
	020	WUDAP	TF	FB	1.0	194.9						AA 01700		E F
	021	SKEPS	TF	FB	0.3	194.9		3.00				AA 00980 GS 00992		E S
	030	RW19	TF	FO	0.3	194.9		3.00				AT 00165		GY M
	040		CA	FB		194.9						AA 00526		M
	050	HEGOG	DF	FO								AA 02000		EY
	060	HEGOG	HM	FO		014.8			R			AA 02000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
OZIGE	N333218.71	W0911532.09
HEGOG	N330920.67	W0912217.67
SKEPS	N332340.33	W0911805.13
WUDAP	N332549.98	W0911726.90

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW19	N332108.60	W0911849.83	00125	40

CITY AND STATE LAKE VILLAGE, AR	ELEVATION: 126 TDZE: 125	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 19, AMDT 1 2 MARCH 2017	SUP: QUALITY
	AIRPORT NAME: LAKE VILLAGE MUNI			AMDT: 4 ORIGINAL
				DATED: 09/17/2015