

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>						<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
AFTON						FOUR	AFTON4.GIGSE	THREE	07/01/2016	19 JULY 2018
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>					
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>					

DP ROUTE DESCRIPTION:

TAKEOFF RWY 34: CLIMB DIRECT WOLEN, THEN ON DEPICTED ROUTE TO GIGSE, MAINTAIN 16000 OR ATC ASSIGNED ALTITUDE; EXPECT CLEARANCE TO FILED ALTITUDE FIVE MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>

PROCEDURAL DATA NOTES:

NOTE: RNAV-1

NOTE: GPS REQUIRED.

TAKEOFF MINIMUMS:

RWY 16: NA. OBSTACLES.

RWY 34, STANDARD WITH MINIMUM CLIMB OF 375 FT PER NM TO 8100.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 34, FENCE BEGINNING 160 FT FROM DER, 412 FT FROM DER, UP TO 6200 FT MSL. POLE 474 FT FROM DER, 364 FT RIGHT OF CENTERLINE, 5 FT AGL/6205 FT MSL. TREES BEGINNING 1038 FT FROM DER, 428 FT RIGHT OF CENTERLINE, UP TO 6238 FT MSL. TREES BEGINNING 1065 FT FROM DER, 324 FT LEFT OF CENTERLINE, UP TO 6218 FT MSL. TREES, TRANSMISSION LINE BEGINNING 1101 FT FROM DER, 279 FT LEFT OF CENTERLINE, UP TO 6229 FT MSL. TREES, TRANSMISSION LINES, TRAVERSE WAY BEGINNING 1104 FT FROM DER, 408 FT RIGHT OF CENTERLINE, UP TO 6246 FT MSL.

CONTROLLING OBSTACLES:

RWY 34: 7578 MSL AAO 424755.07N/1105455.71W.

OBSTACLES MANDATING ODP ROUTE DEVELOPEMENT: RWY 34: 10092 FT MSL AAO 424315.00N/1105109.00W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KAFO 14E EPOCH YR: 2000

DME/DME ASSESSMENT: NOT CONDUCTED

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
---------------------	-------------	--------------



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
AFTON	FOUR	AFTON4.GIGSE	THREE	07/01/2016	19 JULY 2018
AFTON MUNI			AFTON		WY

COMMUNICATIONS:
ZLC, CTAF

FIXES AND/OR NAVAIDS:

REMARKS:

FLIGHT INSPECTED BY:

GARY J VEER

Digitally signed by

ADOLFO D URRUTIA

May 24, 2018

OFFICE SYMBOL:

FICO

DATE:

05/22/18

DEVELOPED BY:

DAVID TEFFETELLER (KWEKU DONKOR)

Digitally signed by

ADOLFO D URRUTIA

May 24, 2018

OFFICE SYMBOL:

AJV-5433

DATE:

02/27/2018

APPROVED BY:

PATRICK MULQUEEN

Digitally signed by

ADOLFO D URRUTIA

May 24, 2018

OFFICE SYMBOL:

AJV-5430

DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A

☐

ALPA

☒

AOPA

☒

APA

☐

HAI

☐

NBAA

☒

OTHER:

ZLC, CASPER FSS, WY AERO

CHANGES - REASONS:

1. CHANGED FROM "CLIMB TO 13000 DIRECT WOLEN, AND VIA TRACK 331.95 TO FRIDM, THEN ON 011.80 TRACK TO JAC VOR/DME" TO "TAKEOFF RWY 34: CLIMB DIRECT WOLEN, THEN ON DEPICTED ROUTE TO GIGSE, MAINTAIN 16000 OR ATC ASSIGNED ALTITUDE;" - TO DECONFLICT KAFO AND KJAC TRAFFIC PER ATC REQUEST AND NEW OBSTACLE EVALUATION.
2. CHANGED COMPUTER CODE FROM AFTON3.JAC TO AFTON4.GIGSE. CHANGED DP NUMBER FORM 3 TO 4 - JAC VOR/DME REMOVED FROM DP.
3. CHANGED TAKEOFF MINIMUMS FROM "RWY 34, STANDARD WITH MINIMUM CLIMB OF 330 FT PER NM TO 10700" TO "RWY 34, STANDARD WITH MINIMUM CLIMB OF 375 FT PER NM TO 8100".
4. CHANGED CONTROLLING OBSTACLE FROM "RWY 34: 7439 MSL AAO 424754.10N/1105501.95W, 10303 MSL AAO 430427.50N/1105519.10W" TO "RWY 34: 7578 MSL AAO 424755.07N/1105455.71W , OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 34: 10092 FT MSL AAO 424315.00N/1105109.00W - NEW OBSTACLE EVALUATION.
5. UPDATED TAKEOFF OBSTACLES NOTES - NEW OBSTACLES EVALUATION.

QUALITY
24
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
AFTON		FOUR		AFTON4.GIGSE		THREE		07/01/2016	19 JULY 2018
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RWY34 (AER)	424156.89N/1105631.94W	N							
WOLEN	424606.31N/1105631.06W	Y	FB	DF		4.16			CG 375 FT/NM TO 8100
FRIDM	430723.66N/1110347.46W	Y	FB	TF	345.95	21.94			
GIGSE	431335.66N/1111312.78W	Y	FB	TF	312.01	9.27			

