

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Distances are in nautical miles (NM). Graphic depictions attached.

This is a **CORRECTED COPY** of the procedure
previously published in NFDD 076.

Arrival Name LNDHY (RNAV)	Number ONE	STAR Computer Code LNDHY.LNDHY1	Superseded Number NONE	Dated	Effective Date 20JUNE2019
-------------------------------------	----------------------	---	----------------------------------	-------	-------------------------------------

TRANSITION ROUTES:

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	MAA	Crossing Altitudes / Fixes
APACK	APACK.LNDHY1	APACK	APACK						AT/ABOVE FL280
			UNADY	165.36	75.95	15000	1200		AT/ABOVE 16000
			LNDHY	165.40	96.00	9000	1200		AT/ABOVE 9000
BITTA	BITTA.LNDHY1	BITTA	BITTA						AT/ABOVE FL280
			BIKUZ	183.47	49.27	15000	1200		AT/ABOVE 16000
			LNDHY	183.34	96.02	9000	1200		AT/ABOVE 9000
DENNS	DENNS.LNDHY1	DENNS	DENNS						AT/ABOVE FL280
			DEKUM	227.51	46.89	15000	1200		AT/ABOVE 16000
			LNDHY	230.70	97.29	9000	1200		AT/ABOVE 9000
FITES	FITES.LNDHY1	FITES	FITES						AT/ABOVE FL280
			FEKIK	266.92	76.87	15000	1200		AT/ABOVE 16000
			LNDHY	266.44	100.00	9000	1200		AT/ABOVE 9000
ZIGIE	ZIGIE.LNDHY1	ZIGIE	ZIGIE						AT/ABOVE FL280
			LNDHY	149.85	198.48	9000	1200		AT/ABOVE 9000

ARRIVAL ROUTE DESCRIPTION:

FROM LNDHY ON TRACK 204.84/11.08 TO CROSS MUNJU AT OR ABOVE 7000 AND AT 220 KIAS, THEN ON TRACK 204.46/9.61 TO CROSS HOMAI AT 5000 AND AT 210 KIAS, THEN ON TRACK 204.46. EXPECT RNAV (RNP)/ILS/VISUAL APPROACH LANDING RWY 2, AS ASSIGNED BY ATC.

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED

NOTE: RNAV 1

NOTE: GPS REQUIRED

NOTE: TURBOJET AND TURBOPROP AIRCRAFT ONLY

NOTE: FOR NON-RNP AR AIRCRAFT, EXPECT RADAR VECTORS TO FINAL APPROACH COURSE OR VISUAL APPROACH.

FIXES AND/OR HOLDING PATTERNS:

COMMUNICATIONS:

OGG ATIS, HCF CENTER, TWR, GND CON.

AIRPORTS SERVED:

KAHULUI, KAHULUI, HAWAII (PHOG)



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Distances are in nautical miles (NM). Graphic depictions attached.

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
LNDHY (RNAV)	ONE	LNDHY.LNDHY1	NONE		20JUNE2019

LOST COMMUNICATIONS PROCEDURE:REMARKS:ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: UNSAT.

MAG VAR: PHOG 11E/1990

CHART AT HOMAI TERMINUS: PHOG LDG RWY 2.

FLIGHT INSPECTED BY:

KIM BROWN

Name

Organization

4/4/2019

Date

*Digitally signed by***JACOB POWERS**

May 08, 2019

Signature

DEVELOPED BY:

JOSEPH ZEDER

Name

AJV-5442

Organization

12/06/2018

Date

*Digitally signed by***JACOB POWERS**

May 08, 2019

Signature

APPROVED BY:

MARLON ROBINSON, MANAGER

Name

AAJV-5440JV-5440

Organization

Date

*Digitally signed by***JACOB POWERS**

May 08, 2019

Signature

CHANGES:REASONS:

04/08/20196: THIS IS AN UPDATED COPY OF THE FORM DEVELOPED ON 12/14/2018.

1. KAHULUI AIRPORT NAME CHANGED TO KAHULUI.

5/8/2019: THIS IS A CORECTED COPY OF THE FORM APPROVED ON 4/8/2019.

1. HCF APP CON CHANGED TO HCF CENTER IN COMMUNICATIONS.

QUALITY
13
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STAR (DATA RECORD)

Arrival Name LNDHY (RNAV)	Number ONE	STAR Computer Code LNDHY.LNDHY1		Superseded Number NONE		Dated	Effective Date 20JUNE2019		
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
En Route Transition									
APACK	240237.33N / 1561910.35W	Y		IF			AT/ABOVE FL280		APACK.LNDHY1
UNADY	224634.00N / 1561357.00W	Y	FB	TF	176.36	75.95	AT/ABOVE 16000		
LNDHY	211025.00N / 1560730.00W	Y	FB	TF	176.40	96.00	AT/ABOVE 9000	AT 250K	
En Route Transition									
BITTA	233140.91N / 1552843.81W	Y		IF			AT/ABOVE FL280		BITTA.LNDHY1
BIKUZ	224348.00N / 1554203.00W	Y	FB	TF	194.47	49.27	AT/ABOVE 16000		
LNDHY	211025.00N / 1560730.00W	Y	FB	TF	194.34	96.02	AT/ABOVE 9000	AT 250K	
En Route Transition									
DENNS	222148.24N / 1535250.10W	Y		IF			AT/ABOVE FL280		DENNS.LNDHY1
DEKUM	215708.00N / 1543551.00W	Y	FB	TF	238.51	46.89	AT/ABOVE 16000		
LNDHY	211025.00N / 1560730.00W	Y	FB	TF	241.70	97.29	AT/ABOVE 9000	AT 250K	
En Route Transition									
FITES	204740.40N / 1530002.28W	Y		IF			AT/ABOVE FL280		FITES.LNDHY1
FEKIK	205758.75N / 1542123.73W	Y	FB	TF	277.92	76.87	AT/ABOVE 16000		
LNDHY	211025.00N / 1560730.00W	Y	FB	TF	277.44	100.00	AT/ABOVE 9000	AT 250K	
En Route Transition									
ZIGIE	241849.30N / 1571707.30W	Y		IF			AT/ABOVE FL280		ZIGIE.LNDHY1
LNDHY	211025.00N / 1560730.00W	Y	FB	TF	160.85	198.48	AT/ABOVE 9000	AT 250K	
Common Route									
LNDHY	211025.00N / 1560730.00W	Y		IF			AT/ABOVE 9000	AT 250K	LNDHY.LNDHY1
MUNJU	210124.00N / 1561426.11W	Y	FB	TF	215.84	11.08	AT/ABOVE 7000	AT 220K	
HOMAI	205332.33N / 1562023.47W	Y	FO	TF	215.46	09.61	AT 5000	AT 210K	
PHOG				FM	215.46		AT 5000		RECOMMENDED NAVAID: OGG VORTAC

QUALITY
16
CHECKED