

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES												MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		RNP: DA (DO NOT EXCEED 185 KIAS UNTIL MAWGO) CLIMB TO 5400 ON TRACK 037.98 TO KILTE, RIGHT TURN TO MAWGO, THEN TRACK 157.46 TO CAUDE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 298.27 INBOUND. CHART: ASR. DISTANCE TO THLD FROM 362 HAT: 1.00 NM. CHART MINIMUM 5700 AT MOZFO. CHART MINIMUM 6100 AT QURTR. CHART MINIMUM 6100 AT TEXAZ. CHART MINIMUM 5200 AT VERRO. CHART MINIMUM 5200 AT WESTX. CHART P-47. CHART KTDW IN PLAN AND PROFILE VIEWS. #TCH 3651.0 (DO NOT CHART). ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S											
QURTR (IF)		DONSS (TF) (FB) (RNP 1.00)		218.06 / 6.75				5800													
DONSS		HUBUG (RF) (FB) (RNP 1.00)		(2.65 NM RADIUS CCW (CFRQX))/4.16				5200													
HUBUG		PUKTE (RF) (FB) (RNP 1.00)		(2.58 NM RADIUS CCW (CFLRB))/2.17				5100													
PUKTE		CUBIB (RF) (FB) (RNP 1.00)		(2.58 NM RADIUS CCW (CFFPW))/1.87				4600													
TEXAZ (IF)		HUBUG (TF) (FB) (RNP 1.00)		127.83 / 6.80				5200													
(SEE FORM 8260-10)																					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT CUBIB 3. FAC: 037.96 FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: CUBIB 4600 5. DIST TO THLD FROM OM: 2.98 MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 4600 GS ALT AT: CUBIB 4600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 44.4 # 34:1 IS CLEAR 8. MSA FROM: RW04 6100																		MAG VAR: 8E		EPOCH YEAR: 2000	
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD									
CATEGORY =====>		A		B		C		D		E											
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
AUTHORIZATION REQUIRED																					
RNP 0.12 DA	3969	4000	362	3969	4000	362	3969	4000	362	3969	4000	362									
RNP 0.30 DA	4019	5000	412	4019	5000	412	4019	5000	412	4019	5000	412									
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -14C (7F) OR ABOVE 53C (128F). CHART NOTE: RF REQUIRED. CHART NOTE: GPS REQUIRED. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). (CONTINUED ON PAGE 2)																					
CITY AND STATE		ELEVATION: 3607 TDZE: 3607				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:						SUP:							
AMARILLO, TX		AIRPORT NAME:						RNAV (RNP) Z RWY 4, AMDT 1						AMDT: ORIG-A							
		RICK HUSBAND AMARILLO INTL						12 OCTOBER 2017						DATED 06/30/2011							

QUALITY
25
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33				
TERMINAL ROUTES, (CONT.):				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
VERRO (IF)	PLNZE (TF) (FB) (RNP 1.00)	218.10 / 6.78	5100	
PLNZE	VASSY (RF) (FB) (RNP 1.00)	(2.63 NM RADIUS CW (CFLTT))/4.13	5100	
VASSY	CUBIB (RF) (FB) (RNP 1.00)	(2.58 NM RADIUS CW (CFDZG))/4.05	4600	
WESTX (IF)	VASSY (TF) (FB) (RNP 1.00)	308.06 / 7.19	5100	
MOZFO (IF)	JOPNI (TF) (FB) (RNP 1.00)	037.89 / 6.02	5100	
JOPNI	CUBIB (TF) (FB) (RNP 1.00)	037.94 / 1.82	4600	
CUBIB (FAF)	RW04 (MAP) (TF) (FO) (RNP 0.30)	037.96 / 2.98		
RW04 (MAP)	KILTE (TF) (FB) (RNP 1.00)	037.98 / 5.71		
KILTE	MAWGO (RF) (FB) (RNP 1.00)	(3.54 NM RADIUS CW (CFFLQ)) / 7.38		
MAWGO	CAUDE (TF) (FO) (RNP 1.00)	157.46 / 8.48	5400	
NOTES, (CONT.): CHART PLANVIEW NOTE AT DONSS: MAX 210 KIAS UNTIL CUBIB. CHART PLANVIEW NOTE AT HUBUG: MAX 210 KIAS UNTIL CUBIB. CHART PLANVIEW NOTE AT PLNZE: MAX 210 KIAS UNTIL CUBIB. CHART PLANVIEW NOTE AT VASSY: MAX 210 KIAS UNTIL CUBIB				
CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.				
FOR INOPERATIVE ALS, INCREASE RNP 0.30 ALL CATS VISIBILITY TO 1 3/8 SM. CHART PLANVIEW NOTE: RNAV 1-GPS OR RADAR REQUIRED.				
QUALITY 25 CHECKED				
CITY AND STATE AMARILLO, TX	ELEVATION: 3607 AIRPORT NAME: RICK HUSBAND AMARILLO INTL	TDZE: 3607	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 4, AMDT 1 12 OCTOBER 2017
SUP:				AMDT: ORIG-A
DATED:				06/30/2011

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
**RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
25
CHECKED

CITY AND STATE

AMARILLO, TX

ELEVATION: 3607

TDZE: 3607

AIRPORT NAME:

RICK HUSBAND AMARILLO INTL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (RNP) Z RWY 4, AMDT 1

12 OCTOBER 2017

SUP:

AMDT: **ORIG-A**

DATED: **06/30/2011**