

<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>				<b>RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		<b>RNP: DA</b>  CLIMB TO 5400 ON TRACK 129.46 TO PAMPE AND TRACK 104.55 TO CAUDE AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD SE, RT, 298.27 INBOUND. CHART: ASR. DISTANCE TO THLD FROM 373 HAT: 1.01 NM. CHART MINIMUM 5200 AT BITNE CHART MINIMUM 5700 AT FLITE CHART MINIMUM 6100 AT JETIM CHART MINIMUM 6100 AT ROUTE CHART MINIMUM 6100 AT WONET #TCH 3655.7 (DO NOT CHART) CHART P-47 CHART KTDW IN PLAN AND PROFILE VIEWS. ROUTE TYPE: A, H ROUTE TYPE QUALIFIER 1: F ROUTE TYPE QUALIFIER 2: S							
BITNE (IF)		LHORN (TF) (FB) (RNP 1.00)		308.95 / 6.48				5100									
LHORN		SIXTY (RF) (FB) (RNP 1.00)		(2.68 NM RADIUS CCW (CFVDF))/4.15				5100									
SIXTY		JBEAZ (RF) (FB) (RNP 1.00)		(2.54 NM RADIUS CCW (CFFRN))/1.64				4900									
JBEAZ		SIIXX (RF) (FB) (RNP 1.00)		(2.58 NM RADIUS CCW (CFPGN))/2.41				4600									
FLITE (IF) (SEE FORM 8260-10)		WWOOD (TF) (FB) (RNP 1.00)		310.13 / 6.49				5200									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT SIIXX 3. FAC: <u>129.44</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: <u>SIIXX 4600</u> 5. DIST TO THLD FROM OM: <u>2.96</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>4600</u> GS ALT AT: <u>SIIXX 4600</u> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>52.4 #</u> <u>34:1 IS CLEAR</u> 8. MSA FROM: <u>RW13 6100</u>										MAG VAR: 8E		EPOCH YEAR: 2000					
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD					
CATEGORY =====>		A		B		C		D		E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
AUTHORIZATION REQUIRED																	
RNP 0.30 DA	3976	1 1/4	373	3976	1 1/4	373	3976	1 1/4	373	3976	1 1/4	373					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -14C (7F) OR ABOVE 51C (124F). CHART NOTE: GPS REQUIRED. CHART PLANVIEW NOTE ADJACENT TO BITNE: RF REQUIRED. CHART PLANVIEW NOTE ADJACENT TO FLITE: RF REQUIRED. (CONTINUED ON PAGE 2)																	
CITY AND STATE <b>AMARILLO, TX</b>		ELEVATION: 3607 TDZE: 3603 AIRPORT NAME: <b>RICK HUSBAND AMARILLO INTL</b>				FACILITY IDENTIFIER: <b>RNAV</b>		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (RNP) Z RWY 13, AMDT 1 12 OCTOBER 2017</b>						SUP: AMDT: <b>ORIG-A</b> DATED <b>06/30/2012</b>			

QUALITY  
25  
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33				
TERMINAL ROUTES, (CONT.):				
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
WWOOD	PAHNN (RF) (FB) (RNP 1.00)	(2.64 NM RADIUS CW (CFVST))/4.07	5100	
PAHNN	SSBEE (RF) (FB) (RNP 1.00)	(2.58 NM RADIUS CW (CFVQG))/1.72	4900	
SSBEE	SIIXX (RF) (FB) (RNP 1.00)	(2.58 NM RADIUS CW (CFVCX))/2.38	4600	
JETIM (IF)	PAHNN (TF) (FB) (RNP 1.00)	038.31 / 6.74	5100	
ROUTE (IF)	SIXTY (TF) (FB) (RNP 1.00)	220.09 / 7.11	5100	
WONET (IF)	CEMTU (TF) (FB) (RNP 1.00)	129.34 / 7.20	5800	
CEMTU	SIIXX (TF) (FB) (RNP 0.70)	129.40 / 5.14	4600	
SIIXX (FAF)	RW13 (MAP) (TF) (FO) (RNP 0.30)	129.44 / 2.96		
RW13 (MAP)	PAMPE (TF) (FB) (RNP 1.00)	129.46 / 6.72		
PAMPE	CAUDE (TF) (FO) (RNP 1.00)	104.55 / 6.31	5400	
NOTES, (CONT.): CHART PLANVIEW NOTE ADJACENT TO JETIM: RF REQUIRED. CHART PLANVIEW NOTE ADJACENT TO ROUTE: RF REQUIRED. CHART PLANVIEW NOTE AT SIXTY: MAX 210 KIAS UNTIL JBEAZ. CHART PLANVIEW NOTE AT LHORN: MAX 210 KIAS UNTIL JBEAZ. CHART PLANVIEW NOTE AT JBEAZ: MAX 180 KIAS UNTIL SIIXX. CHART PLANVIEW NOTE AT WWOOD: MAX 210 KIAS UNTIL SSBEE. CHART PLANVIEW NOTE AT PAHNN: MAX 210 KIAS UNTIL SSBEE. CHART PLANVIEW NOTE AT SSBEE: MAX 180 KIAS UNTIL SIIXX. CHART PLANVIEW NOTE AT WONET: (RNP 0.70). CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS. CHART PLANVIEW NOTE: RNAV 1-GPS OR RADAR REQUIRED.				
QUALITY 25 CHECKED				
CITY AND STATE AMARILLO, TX	ELEVATION: 3607 AIRPORT NAME: RICK HUSBAND AMARILLO INTL	TDZE: 3603	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 13, AMDT 1 12 OCTOBER 2017
SUP:				AMDT: ORIG-A
DATED:				06/30/2012

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV (RNP) - STANDARD,  
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY  
25  
CHECKED

CITY AND STATE  
**AMARILLO, TX**

**ELEVATION: 3607 TDZE: 3603**  
AIRPORT NAME:  
**RICK HUSBAND AMARILLO INTL**

FACILITY  
IDENTIFIER:  
**RNAV**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
**RNAV (RNP) Z RWY 13, AMDT 1**  
12 OCTOBER 2017

SUP:  
AMDT: **ORIG-A**  
DATED: **06/30/2012**