

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE			LPV: DA LNAV/VNAV: DA LNAV: RW35 CLIMB TO 3600 DIRECT DUGTE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 170.01 INBOUND. CHART FAS OBST: 1369 TREE 444601N/0894059W DISTANCE TO THLD FROM 200 HAT: 0.55 NM. CHART VDP AT 1.08 NM TO RW35* *LNAV ONLY. WAAS CHANNEL # 93521 REFERENCE PATH ID: W35A CHART CIRCLING ICON. LTP HAE: 338.3 M									
EDGRR			LEERY (TF) (FO) (RNP 2.00)			139.13 / 20.61			3000												
RROBB (IAF)			LEERY (NOPT) (TF) (FB) (RNP 1.00)			307.85 / 5.42			3000												
LEERY (IF/IAF)			JONIS (TF) (FB) (RNP 1.00)			350.06 / 4.62			3000												
JONIS (FAF)			HUREB/2.00 NM TO RW35 (TF) (FB) (RNP 0.30)			350.06 / 3.42															
HUREB/2.00 NM TO RW35			RW35 (MAP) (TF) (FO) (RNP 0.30)			350.06 / 2.00															
(SEE FORM 8260-10)																					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S LEERY, RT, 350.07 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 350.06 FAF: JONIS DIST FAF TO MAP: 5.42 THLD: 5.42 4. MIN. ALT: LEERY 3000, JONIS 3000, HUREB/2.00 NM TO RW35 1900* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3000 GS ALT AT: JONIS 3000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR 8. MSA FROM: RW35 3600																					
												MAG VAR: 0E						EPOCH YEAR: 1985			
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD									
CATEGORY ==>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
LPV DA	1451	1/2	200	1451	1/2	200	1451	1/2	200	1451	1/2	200									
LNAV/VNAV DA	1576	3/4	325	1576	3/4	325	1576	3/4	325	1576	3/4	325									
LNAV MDA	1620	1/2	369	1620	1/2	369	1620	5/8	369	1620	5/8	369									
CIRCLING	1740	1	463	1740	1	463	1740	1 1/2	463	1840	2	563									
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EDGRR ON V26 WESTBOUND.																					
CITY AND STATE				ELEVATION: 1277 TDZE: 1251				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
MOSINEE, WI				AIRPORT NAME:								RNAV (GPS) RWY 35, AMDT 2				AMDT: 1B					
				CENTRAL WISCONSIN								17 AUGUST 2017				DATED 07/23/2015					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW35 (MAP)	1451 MSL (CA)	350.06	
1451 MSL	DUGTE (DF) (FO) (RNP 1.00)		3600



CITY AND STATE
MOSINEE, WI

ELEVATION: 1277 TDZE: 1251
AIRPORT NAME:
CENTRAL WISCONSIN

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 35, AMDT 2
17 AUGUST 2017

SUP:
AMDT: 1B
DATED: 07/23/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCWA
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	444548.5710N
LTP/FTP LONGITUDE	0894016.3705W
LTP/FTP ELLIPSOIDAL HEIGHT	+03383
FPAP LATITUDE	444716.3230N
FPAP LONGITUDE	0894037.9990W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

AA156850

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+03734
FPAP ORTHOMETRIC HEIGHT	+03734

QUALITY
16
CHECKED

CITY AND STATE

MOSINEE, WI

ELEVATION: 1277

TDZE: 1251

AIRPORT NAME:

CENTRAL WISCONSIN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 2

17 AUGUST 2017

SUP:

AMDT:

1B

DATED:

07/23/2015