

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE

MAP: JMS VOR/DME

CLIMB TO 3500 THEN LEFT TURN DIRECT JMS VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD SE, RT, 313.00 INBOUND.
CHART FAS OBST: 1595 TREE 465725N/0984255W
CHART DEVILS LAKE EAST MOA.
CHART VDP AT 1.34 DME
DISTANCE VDP TO THLD 0.97 NM.
CHART CIRCLING ICON.
CHART MAXIMUM ENTRY ALTITUDE 6000.
FAC CROSSES RWY C/L EXTENDED 2988 FT FROM THLD.

- 1. PT R SIDE OF COURSE 302.61 OUTBOUND 3200 FT WITHIN 10 MILES OF JMS VOR/DME (IAF)
- 2. _____
- 3. FAC 122.61 FAF _____ DIST FAF TO MAP _____ THLD _____
- 4. MIN. ALT EMCEC/JMS 2.20 DME 2040
- 8. MSA FROM: JMS VOR/DME 3600

MAG VAR: **4E** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	STANDARD @								
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-13	2040	1	540	2040	1	540	2040	1 1/2	540	2040	1 3/4	540				
CIRCLING	2040	1	540	2040	1	540	2040	1 1/2	540	2300	2 1/2	800				

EMCEC FIX MINIMUMS

S-13	1860	1	360	1860	1	360	1860	1	360	1860	1 1/4	360			
CIRCLING	1960	1	460	1960	1	460	2000	1 1/2	500	2300	2 1/2	800			

NOTES:

CHART NOTE: RWY 13 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

@ CAT D 800-2 1/2



CITY AND STATE JAMESTOWN, ND	ELEVATION: 1500 TDZE: 1500	FACILITY IDENTIFIER: JMS	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 13, AMDT 8A, 12/07/2017	SUP
	AIRPORT NAME: JAMESTOWN RGNL			AMDT 8
				DATE 08/30/2007