

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE

MAP: JMS VOR/DME

CLIMB TO 3100 THEN RIGHT TURN DIRECT JMS VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD SE, RT, 313.00 INBOUND.
CHART FAS OBST: 1630 TANK 465500N/0984130W
CHART VDP AT 1.82 DME
DISTANCE VDP TO THLD 1.10 NM.
CHART CIRCLING ICON.

1. PT L SIDE OF COURSE 136.64 OUTBOUND 3100 FT WITHIN 10 MILES OF JMS VOR/DME (IAF)
2. _____
3. FAC 316.64 FAF _____ DIST FAF TO MAP _____ THLD _____
4. MIN. ALT AMUJO/JMS 2.80 DME 2080
8. MSA FROM: JMS VOR/DME 3600

MAG VAR: **4E** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	STANDARD @								
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-31	2080	1/2	582	2080	1/2	582	2080	1	582	2080	1 1/4	582				
CIRCLING	2080	1	580	2080	1	580	2080	1 3/4	580	2300	2 1/2	800				

AMUJO FIX MINIMUMS

S-31	1900	1/2	402	1900	1/2	402	1900	3/4	402	1900	1	402			
CIRCLING	1960	1	460	1960	1	460	2000	1 1/2	500	2300	2 1/2	800			

NOTES:

@ CAT D 800-2 1/2



CITY AND STATE JAMESTOWN, ND	ELEVATION: 1500 TDZE: 1498	FACILITY IDENTIFIER: JMS	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 31, AMDT 9A, 12/07/2017	SUP
	AIRPORT NAME: JAMESTOWN RGNL			AMDT 9
				DATE 08/27/2009