

**Federal Aviation
Administration**

Transmittal Letter 15-02

December 5, 2014

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
8-Jan-15	SC	Clemson	Oconee County Rgnl	4/6980	11/19/14	RNAV (GPS) RWY 25, AMDT 3

AIRAC Date: 8 JANUARY 2015

FDC 4/6980 CEU IAP OCONEE COUNTY RGNL, CLEMSON, SC. RNAV (GPS) RWY 25, AMDT 3... LNAV/VNAV DA 1141/HAT 250. LNAV HAT 329. CIRCLING CAT C MDA 1640/HAA 749, VIS 2 1/4. CHART TDZE 891 DELETE THRE 874. CHART CIRCLING ICON. CHART ALTERNATE MINIMUMS: CAT C 800-2 1/4 CHANGE BARO-VNAV ADJUSTMENT NOTE TO READ: FOR UNCOMPENSATED BAROVNAV SYSTEMS, LNAV/VNAV NA BELOW -6C (22F) OR ABOVE 54C (130F). CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ANDERSON ALTIMETER SETTING AND INCREASE ALL DA 47 FEET AND ALL MDA 60 FEET; INCREASE LPV ALL CATS, AND LNAV CAT C VISIBILITY 1/8 MILE; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 25, AMDT 3A. 1410312006-PERM