

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE			LPV: DA LNAV/VNAV: DA LNAV: RW13 (DO NOT EXCEED 250 KIAS UNTIL OQUDI) CLIMB TO 7800 THEN CLIMBING RIGHT TURN TO 12400 DIRECT OQUDI AND HOLD, CONTINUE CLIMB-IN-HOLD TO 12400. ADDITIONAL FLIGHT DATA: HOLD N, RT, 168.06 INBOUND. CHART FAS OBST: 7154 TREE 362824N/1054112W. 7717 AAO 363112N/1054724W. DISTANCE TO THLD FROM 200 HAT: 0.55 NM. CHART VDP AT 1.05 NM TO RW13* *LNAV ONLY. WAAS CHANNEL # 97441 REFERENCE PATH ID: W13A CHART CIRCLING ICON. LTP HAE: 2130.1 M									
TELOY			OQUDI (TF) (FO) (RNP 2.00)			006.39 / 12.89			11000												
ZOTOS (IAF)			OQUDI (NOPT) (TF) (FB) (RNP 1.00)			168.73 / 22.92			11000												
OQUDI (IF/IAF)			UJZIN (TF) (FB) (RNP 1.00)			126.28 / 6.39			9000												
UJZIN (FAF)			WORIN/3.10 NM TO RW13 (TF) (FB) (RNP 0.30)			126.33 / 2.91															
WORIN/3.10 NM TO RW13			RW13 (MAP) (TF) (FO) (RNP 0.30)			126.33 / 3.10															
(SEE FORM 8260-10)																					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N OQUDI, LT, 168.06 INBOUND, 11000 FT. IN LIEU OF PT (IAF) 3. FAC: 126.33 FAF: UJZIN DIST FAF TO MAP: 6.01 THLD: 6.01 4. MIN. ALT: OQUDI 11000, UJZIN 9000, WORIN/3.10 NM TO RW13 8060* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 9000 GS ALT AT: UJZIN 9000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 37.1 34:1 IS CLEAR 8. MSA FROM: RW13 14400																		MAG VAR: 11E		EPOCH YEAR: 1985	
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @									
CATEGORY >>>>>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
LPV DA	7258	3/4	200	7258	3/4	200	7258	3/4	200	7258	3/4	200									
LNAV/VNAV DA	7346	7/8	288	7346	7/8	288	7346	7/8	288	7346	7/8	288									
LNAV MDA	7420	1	362	7420	1	362	7420	1	362	7420	1	362									
CIRCLING	7600	1	505	7640	1	545	7920	2 1/2	825	8020	3	925									
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -29C (-20F) OR ABOVE 47C (118F). @ CAT C 900-2 1/2, CAT D 1000-3 CHART NOTE: DME/DME RNP-0.3 NA.																					
CITY AND STATE TAOS, NM				ELEVATION: 7095 TDZE: 7058 AIRPORT NAME: TAOS RGNL				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG, 12/07/2017				SUP:					
																AMDT: NONE					
																DATED					

QUALITY
 24
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW13 (MAP)	7800 MSL (CA)	126.33	7800
7800 MSL	OQUDI (DF) (FO) (RNP 1.00)		12400

QUALITY
24
CHECKED

CITY AND STATE
TAOS, NM

ELEVATION: 7095 TDZE: 7058
AIRPORT NAME:
TAOS RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 13, ORIG, 12/07/2017

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSKX
RUNWAY	RW13
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W13A
LTP/FTP LATITUDE	362721.8895N
LTP/FTP LONGITUDE	1054101.2640W
LTP/FTP ELLIPSOIDAL HEIGHT	+21301
FPAP LATITUDE	362616.2230N
FPAP LONGITUDE	1053946.5010W
THRESHOLD CROSSING HEIGHT (TCH)	00037.1
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0136
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 EB7F15F1

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+21480
FPAP ORTHOMETRIC HEIGHT	+21480

QUALITY
24
CHECKED

CITY AND STATE TAOS, NM	ELEVATION: 7095 AIRPORT NAME: TAOS RGNL	TDZE: 7058 RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG, 12/07/2017	SUP:
				AMDT: NONE
				DATED: