

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**LOC STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
STV VORTAC	ZOTEP INT	210.73 / 23.47	3600
CSI VORTAC	ZOTEP INT	088.24 / 11.92	3600

**MAP: 6.19 NM AFTER ZOTEP INT**

**CLIMB TO 2100 THEN CLIMBING LEFT TURN TO 4100 DIRECT CSI VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4100.**

ADDITIONAL FLIGHT DATA:  
**HOLD W, LT, 088.24 INBOUND.**  
**CHART FAS OBST: 1649 WNDML 295747N/0990412W**  
**CHART: 1750 TOWER 295617N/0990211W**  
**CHART CIRCLING ICON.**  
**ZOTEP TO RW30: 3.00/40.**  
**CHART IN PLANVIEW: (CFBHB)**  
**(295125.25N/0985544.70W).**

- PT \_\_\_\_\_ SIDE OF COURSE \_\_\_\_\_ OUTBOUND \_\_\_\_\_ FT WITHIN \_\_\_\_\_ MILES OF \_\_\_\_\_ (IAF)
- HOLD SE ZOTEP, LT, 304.55 INBOUND, 3600 FT. IN LIEU OF PT (IAF)**
- FAC 304.55 FAF ZOTEP INT DIST FAF TO MAP 6.19 THLD 6.19
- MIN. ALT ZOTEP INT 3600, ZABOS INT 2360
- MSA FROM: **CSI VORTAC 4100**

MAG VAR: **6E** EPOCH YEAR: **2005**

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A X								
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
<b>S-30</b>	2360	1	771	2360	1 1/4	771	2360	2 1/2	771	2360	2 1/2	771			
<b>CIRCLING</b>	2360	1	743	2360	1 1/4	743	2380	2 1/2	763	2540	3	923			

**ZABOS FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)**

<b>S-30</b>	1900	1	311	1900	1	311	1900	1	311	1900	1	311			
<b>CIRCLING</b>	2260	1	643	2340	1	723	2380	2 1/4	763	2540	3	923			

NOTES:

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON CSI VORTAC AIRWAY RADIALS 105 CW 138.  
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON STV VORTAC AIRWAY RADIAL 151.



CITY AND STATE <b>KERRVILLE, TX</b>	ELEVATION: 1617 TDZE: 1589	FACILITY IDENTIFIER: <b>I-ERV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>LOC RWY 30, AMDT 5</b> 27 APRIL 2017	SUP
	AIRPORT NAME: <b>KERRVILLE MUNI/LOUIS SCHREINER FIELD</b>			AMDT <b>4A</b>
				DATE <b>04/05/2012</b>

**LOC STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE <b>KERRVILLE, TX</b>	ELEVATION: 1617      TDZE: 1589 AIRPORT NAME: <b>KERRVILLE MUNI/LOUIS SCHREINER FIELD</b>	FACILITY IDENTIFIER: <b>I-ERV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>LOC RWY 30, AMDT 5</b> 27 APRIL 2017	SUP:
				AMDT: <b>4A</b>
				DATED: <b>04/05/2012</b>