

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH											
FROM			TO			COURSE AND DISTANCE				ALTITUDE		MAP: 4.93 NM AFTER JIFIE/ANX 8.80 DME/RADAR OR AT CATRU/ANX 13.73 DME FIX									
ANX VORTAC (IF/IAF)			JIFIE/ANX 8.80 DME/RADAR			229.00 / 8.80				2500		CLIMBING LEFT TURN TO 2900 DIRECT ANX VORTAC AND HOLD.									
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 268.00 INBOUND. CHART FAS OBST: 1162 TOWER 390038N/0941807W. 1191 AAO 390018N/0941642W CHART CIRCLING ICON. FAC CROSSES RWY 18/36 342 FEET LEFT OF RWY 18 THLD.											
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																					
2. PROFILE STARTS AT ANX VORTAC																					
3. FAC 229.00 FAF JIFIE/ANX 8.80 DME/RADAR										DIST FAF TO MAP 4.93 THLD											
4. MIN. ALT ANX VORTAC 2900, JIFIE 2500																					
8. MSA FROM: ANX VORTAC 3100										MAG VAR: 7E EPOCH YEAR: 1965											
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E							
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
CIRCLING		1440	1	436	1540	1	536	1780	2 1/4	776	1780	2 1/2	776								
NOTES:																					
CHART NOTE: DME OR RADAR REQUIRED.										@ NA WHEN LOCAL WEATHER NOT AVAILABLE.											
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ANX VORTAC AIRWAY RADIALS 153 CW 236.										@ CAT C 800-2 1/4, CAT D 800-2 1/2											
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLES B. WHEELER DOWNTOWN ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET, AND CAT C AND D VISIBILITY 1/4 MILE.																					
CITY AND STATE		ELEVATION: 1004			TDZE:			FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP		VOR/DME-A				
LEE'S SUMMIT, MO								ANX		VOR-A, AMDT 1, 02/01/2018					AMDT		ORIG-A				
		LEE'S SUMMIT MUNI													DATE		06/05/2008				



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
6
CHECKED

CITY AND STATE

LEE'S SUMMIT, MO

ELEVATION: 1004

TDZE:

AIRPORT NAME:

LEE'S SUMMIT MUNI

FACILITY
IDENTIFIER:

ANX

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR-A, AMDT 1, 02/01/2018

SUP: VOR/DME-A

AMDT: ORIG-A

DATED: 06/05/2008