

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV: RW03						
HANDE (IAF)		HANUR (NOPT) (TF) (FB) (RNP 1.00)		073.71 / 9.77			4000		CLIMB TO 1200, THEN CLIMBING LEFT TURN TO 4000 DIRECT HANUR AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4000.						
HANUR (IF/IAF)		CEKLA (TF) (FB) (RNP 1.00)		026.05 / 6.25			2400								
CEKLA (FAF)		WIKMU/2.80 NM TO RW03 (TF) (FB) (RNP 0.30)		026.12 / 2.87											
WIKMU/2.80 NM TO RW03		RW03 (MAP) (TF) (FO) (RNP 0.30)		026.12 / 2.80											
RW03 (MAP)		1200 MSL (CA)		026.12			1200		ADDITIONAL FLIGHT DATA: CHART FAS OBST: 879 TREE 333214N/0861455W CHART R-2101. CHART R-2102 A,B,C. CHART VDP AT 1.88 NM TO RW03* *LNAV ONLY. WAAS CHANNEL # 70540 REFERENCE PATH ID: W03A CHART CIRCLING ICON. DISTANCE TO THLD FROM 351 HAT: 0.91 NM LTP HAE: 118.3 M						
1200 MSL		HANUR (DF) (FO) (RNP 1.00)					4000								
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 4W EPOCH YEAR: 2020					
2. HOLD SW HANUR, RT, 026.05 INBOUND, 4000 FT. IN LIEU OF PT (IAF)															
3. FAC: 026.12 FAF: CEKLA DIST FAF TO MAP: 5.67 THLD: 5.67															
4. MIN. ALT: HANUR 4000, CEKLA 2400, WIKMU/2.80 NM TO RW03 1440*															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: 2400 GS ALT AT: CEKLA 2400 OM: _____ MM: _____ IM: _____															
7. GS ANGLE: 3.10 TCH: 52.0 34:1 IS NOT CLEAR															
8. MSA FROM: RW03 4000															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	835	1 1/8	351	835	1 1/8	351	835	1 1/8	351	835	1 1/8	351			
LNAV MDA	1140	1	656	1140	1	656	1140	1 7/8	656	1140	1 7/8	656			
CIRCLING	1180	1	695	1180	1	695	1240	2 1/4	755	1340	2 3/4	855			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HANDE ON V159-521 NORTHWEST BOUND. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: VDP NA WHEN USING ANNISTON ALTIMETER SETTING. (CONTINUED ON PAGE 2)															
CITY AND STATE PELL CITY, AL		ELEVATION: 485 TDZE: 484 AIRPORT NAME: ST CLAIR COUNTY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 3 27 APRIL 2017				SUP: 4 AMDT: 2C DATED 07/25/2013					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: RWY 3, HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ANNISTON ALTIMETER SETTING AND INCREASE ALL DA 63 FEET AND ALL VISIBILITY 1/4 SM, INCREASE ALL MDA 80 FEET AND LNAV CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT C/D 1/4 SM.

CITY AND STATE
PELL CITY, AL

ELEVATION: 485 TDZE: 484
AIRPORT NAME:
ST CLAIR COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 3, AMDT 3
27 APRIL 2017

SUP: 4
AMDT: 2
DATED: 07/25/2013

QUALITY
CHECKED

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KPLR
RUNWAY	RW03
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W03A
LTP/FTP LATITUDE	333310.9820N
LTP/FTP LONGITUDE	0861506.6270W
LTP/FTP ELLIPSOIDAL HEIGHT	+01183
FPAP LATITUDE	333433.6630N
FPAP LONGITUDE	0861426.4370W
THRESHOLD CROSSING HEIGHT (TCH)	00052.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.10
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1296
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 64B580FF

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+01473
FPAP ORTHOMETRIC HEIGHT	+01473

QUALITY
16
CHECKED

CITY AND STATE PELL CITY, AL	ELEVATION: 485 AIRPORT NAME: ST CLAIR COUNTY	TDZE: 484 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 3 27 APRIL 2017	SUP:
				AMDT: 2C
				DATED: 07/25/2013