

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33									Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE			LNAV: KOBAH									
BOIER			KOZUL (TF) (FB) (RNP 2.00)			318.65 / 11.02			6900			CLIMB TO 5500 DIRECT YOLUY AND ON TRACK 033.19 TO MUHAP AND HOLD.									
KOZUL (IAF)			DOFAD (TF) (FB) (RNP 1.00)			300.80 / 5.41			5900												
AHCIN (IAF)			DOFAD (TF) (FB) (RNP 1.00)			119.98 / 5.47			5900												
DOFAD (IF)			ELEME (TF) (FB) (RNP 1.00)			031.92 / 6.04			4500												
ELEME (FAF)			JNIFR/4.70 NM TO KOBAH (TF) (FB) (RNP 0.30)			031.96 / 2.48						ADDITIONAL FLIGHT DATA: HOLD SW, RT, 033.19 INBOUND. CHART FAS OBST: 2779 TREE 385041N/0795421W. ZAROB TO RW05: 3.62/50 CHART CIRCLING ICON CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 13.83 DEGREES. FAC CROSSES RWY C/L EXTENDED 3000 FT FROM THLD.									
(SEE FORM 8260-10)																					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																					
2. PROFILE STARTS AT DOFAD																					
3. FAC: 031.96 FAF: ELEME DIST FAF TO MAP: 7.18 THLD: 7.66																					
4. MIN. ALT: DOFAD 5900, ELEME 4500, JNIFR/4.70 NM TO KOBAH 3700*, ZAROB/3.00 NM TO KOBAH 3360**																					
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																					
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																					
7. GS ANGLE: _____ TCH: 20:1 IS CLEAR 34:1 IS NOT CLEAR																					
8. MSA FROM: KOBAH 6100												MAG VAR: 7W			EPOCH YEAR: 1985						
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT												ALTERNATE: N A						@			
CATEGORY ==>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
LNAV MDA	3040	1 1/4	1068	3040	1 1/2	1068	3040	3	1068		NA										
CIRCLING	3040	1 1/4	1053	3140	1 1/2	1153	3720	3	1733	4020	3	2033									
NOTES: CHART NOTE: CIRCLING RWY 14, 23, 32 NA AT NIGHT.																					
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BUCKHANNON ALTIMETER SETTING AND INCREASE ALL MDA 100 FT. (CONTINUED ON PAGE 2)												@ NA WHEN LOCAL WEATHER NOT AVAILABLE. @ CAT A, B 1400-2, CAT C 1800-3, CAT D 2100-3									
CITY AND STATE ELKINS, WV			ELEVATION: 1987 TDZE: 1972 AIRPORT NAME: ELKINS-RANDOLPH CO-JENNINGS RANDOLPH FLD			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 5, ORIG-A 24 MAY 2018						SUP: AMDT: ORIG DATED 12/17/2009							



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
JNIFR/4.70 NM TO KOBAB	ZAROB/3.00 NM TO KOBAB (TF) (FB) (RNP 0.30)	031.96 / 1.70	
ZAROB/3.00 NM TO KOBAB	KOBAB (MAP) (TF) (FO) (RNP 0.30)	031.96 / 3.00	
KOBAB (MAP)	2387 MSL (CA)	031.96	
2387 MSL	YOLUY (DF) (FB) (RNP 1.00)		
YOLUY	MUHAP (TF) (FO) (RNP 1.00)	033.19 / 9.02	5500

NOTES, (CONT.):

CHART NOTE: * 3800 WHEN USING BUCKHANNON ALTIMETER SETTING

CHART NOTE: ** 3460 WHEN USING BUCKHANNON ALTIMETER SETTING

CHART NOTE: STRAIGHT-IN MINIMUMS NA WHEN USING BUCKHANNON ALTIMETER SETTING

CHART NOTE: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT AHCIN ON V103 NORTH BOUND

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BOIER ON V469 SOUTHEAST BOUND, AND ON V128
EASTBOUND

PBN REQUIREMENTS NOTE: RNP APCH.

QUALITY
16
CHECKED

CITY AND STATE

ELKINS, WV

ELEVATION: 1987

TDZE: 1972

AIRPORT NAME:

ELKINS-RANDOLPH CO-JENNINGS RANDOLPH
FLDFACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 5, ORIG-A

24 MAY 2018

SUP:

AMDT: ORIG

DATED: 12/17/2009