

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: XIHGA/LVZ 15.79 DME							
LVZ VORTAC (IF/IAF)		PANNE/LVZ 11.20 DME		130.50 / 11.20				3400		CLIMBING RIGHT TURN TO 4000 DIRECT LVZ VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 010.00 INBOUND. FAS OBST: 2239 AAO 411147N/0752711W PANNE TO RW13: 3.03/40. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 2817 FROM THLD.							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT LVZ VORTAC _____ 3. FAC 130.50 FAF PANNE/LVZ 11.20 DME _____ DIST FAF TO MAP _____ THLD 4.59 4. MIN. ALT LVZ VORTAC 4000, PANNE 3400 _____ 8. MSA FROM: LVZ VORTAC 4000 _____														MAG VAR: 10W		EPOCH YEAR: 1965	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @					
CATEGORY ==>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-13	2500	1	616	2500	1	616	2500	1 3/4	616	2500	1 3/4	616					
CIRCLING	2500	1	585	2500	1	585	2600	2	685	2660	2 1/2	745					
NOTES: CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON LVZ VORTAC AIRWAY RADIALS 094 CW 190. CHART NOTE: RWY 13 STRAIGHT-IN AND CIRCLING AND CIRCLING TO RWY 23 NA AT NIGHT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WILKES-BARRE/SCRANTON ALTIMETER SETTING (SEE FORM 8260-10)																	
CITY AND STATE				ELEVATION: 1915 THRE: 1884		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP		VOR RWY 13			
MOUNT POCONO, PA				AIRPORT NAME:		LVZ		VORDME RWY 13, AMDT 8 17 OCTOBER 2013				AMDT		7			
				POCONO MOUNTAINS MUNI								DATE		11/18/2010			

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

AND INCREASE ALL MDA 180 FEET; INCREASE S-13 CAT B AND CIRCLING CAT B VISIBILITY 1/4 MILE, S-13 CATS C/D VISIBILITY 3/4 MILE, AND CIRCLING CATS C/D VISIBILITY 1/2 MILE.



CITY AND STATE MOUNT POCONO, PA	ELEVATION: 1915 THRE: 1884 AIRPORT NAME: POCONO MOUNTAINS MUNI	FACILITY IDENTIFIER: LVZ	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: VOR/DME RWY 13, AMDT 8 17 OCTOBER 2013	SUP: VOR RWY 13
				AMDT: 7
				DATED: 11/18/2010