

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW36 LNAV: RW36 CLIMB TO 3300 DIRECT UZZUF AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 175.19 INBOUND. CHART FAS OBST: 1389 BEACON 370907N/0980437W CHART FAS OBST: 1394 TREE 370734N/0980528W WAAS CHANNEL # 86927 REFERENCE PATH ID: W36A HUVSO TO RW36: 3.00/45. CHART: A-562B CHART WICHITA MID-CONTINENT ASOS-3. LTP HAE: 378.4 M											
CARON (IAF)	COXAV (NOPT) (FB)	082.99 / 26.35	3000												
DOREC (IAF)	COXAV (NOPT) (FB)	275.99 / 31.49	3000												
COXAV (IF/IAF)	HUVSO (FB)	355.19 / 6.88	2900												
HUVSO (FAF)	WILEX/2.10 NM TO RW36 (FB)	355.19 / 2.68													
WILEX/2.10 NM TO RW36	RW36 (MAP) (FO)	355.19 / 2.10													
RW36 (MAP)	1740 MSL	355.19													
1740 MSL	UZZUF (FO)		3300												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD S COXAV, RT, 355.19 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>355.19</u> FAF: <u>HUVSO</u> DIST FAF TO MAP: <u>4.78</u> THLD: <u>4.78</u> 4. MIN. ALT: COXAV 3000, HUVSO 2900, WILEX/2.10 NM TO RW36 2040 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: RW36 3600				MAG VAR: 5E EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A		B		C	D	E								
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1740	1	406	1740	1	406	1740	1 1/8	406		NA				
LNAV MDA	1760	1	426	1760	1	426	1760	1 1/4	426		NA				
CIRCLING	1960	1	620	1960	1	620	1960	1 3/4	620		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: USE WICHITA MID-CONTINENT ALTIMETER SETTING: WHEN NOT RECEIVED, USE BLACKWELL, OK ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND INCREASE ALL CAT C VISIBILITIES 1/4 MILE. (SEE FORM 8260-10)															
CITY AND STATE ANTHONY, KS		ELEVATION: 1340 THRE: 1334 AIRPORT NAME: ANTHONY MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 31 MAY 2012				SUP: AMDT: NONE DATED					

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES. (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT DOREC ON V74-516 EASTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CARON ON V190 WESTBOUND AND V12 SOUTHWEST BOUND.

CHART NOTE: CIRCLING NA TO RWYS 10 AND 28.

CHART NOTE: PROCEDURE NA AT NIGHT.

QUALITY
2
CHECKED

CITY AND STATE ANTHONY, KS	ELEVATION: 1340 AIRPORT NAME: ANTHONY MUNI	THRE: 1334 FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 31 MAY 2012	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE 0
 SBAS SERVICE PROVIDER IDENTIFIER 0
 AIRPORT IDENTIFIER KANY
 RUNWAY RW36
 APPROACH PERFORMANCE DESIGNATOR 0
 ROUTE INDICATOR 0
 REFERENCE PATH DATA SELECTOR W36A
 REFERENCE PATH IDENTIFIER (APPROACH ID) 370913.7280N
 LTP/FTP LATITUDE 0980444.7080W
 LTP/FTP LONGITUDE +03784
 LTP/FTP ELLIPSOIDAL HEIGHT 371042.9400N
 FPAP LATITUDE 0980444.3400W
 FPAP LONGITUDE 00045.0
 THRESHOLD CROSSING HEIGHT (TCH) F
 TCH UNITS SELECTOR (METERS OR FEET USED) 03.00
 GLIDEPATH ANGLE (GPA) 106.75
 COURSE WIDTH AT THRESHOLD 1656
 LENGTH OFFSET 40.0
 HORIZONTAL ALERT LIMIT (HAL) 0.0
 VERTICAL ALERT LIMIT (VAL)

CRC REMAINDER

7E92BC0B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K3
 LTP ORTHOMETRIC HEIGHT +04066
 FPAP ORTHOMETRIC HEIGHT +04066

QUALITY
2
CHECKED

CITY AND STATE ANTHONY, KS	ELEVATION: 1340 THRE: 1334 AIRPORT NAME: ANTHONY MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 31 MAY 2012	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE ANTHONY, KS	ELEVATION: 1340 THRE: 1334 AIRPORT NAME: ANTHONY MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 31 MAY 2012	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP KANYK3PR36 RW36 001 0000W36A0N3709137280W09804447080+037840300N3710429400W09804443400106751656000450F4000007E92BC0B
SUSAP KANYK3PR36 RW36 002E +04066+04066LP 86927

SUSAP KANYK3SRW36 K3PG 0 18018003625 M