Federal Aviation Administration

Transmittal Letter 16-23

September 23, 2016

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: \$97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; \$97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; \$97.27 NDB, NDB/DME; \$97.29 ILS, ILS/DME, MLS/RNAV; \$97.31 RADAR SIAPs; \$97.33 RNAV SIAPs; and \$97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10-Nov-16	GA	Swainsboro	East Georgia Regional	6/8366	9/20/16	RNAV (GPS) RWY 14, Amdt 1A

AIRAC Date: 10 NOVEMBER 2016

FDC 6/8366 SBO IAP EAST GEORGIA REGIONAL, SWAINSBORO, GA. RNAV (GPS) RWY 14, AMDT 1A... LPV DA 643 ALL CATS. LNAV/VNAV DA 633 ALL CATS. LNAV HAT 373 ALL CATS. DELETE THRE 324, CHART TDZE 327. DELETE NOTE: WHEN VGSI INOPERATIVE, PROCEDURE NA AT NIGHT. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: RWY 14 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE BACKUP ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VIDILIA ALTIMETER SETTING AND INCREASE LPV DA TO 708, LNAV/VNAV DA TO 698, AND ALL MDA 80 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 SM, LNAV CATS C/D VISIBILITY 3/8 SM, CIRCLING CAT C VISIBILITY 1/2 SM, AND CIRCLING CAT D VISIBILITY 1/4 SM. DELETE NOTE: BARO-VNAV NA WHEN USING VIDALIA ALTIMETER SETTING. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING VIDALIA ALTIMETER SETTING. CHART VDP AT 1.04 NM TO RW14*. *LNAV ONLY DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 41C (105F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). THIS IS RNAV (GPS) RWY 14, AMDT 1B. 1608221456-**PERM**