

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW03 CLIMB TO 3000 DIRECT ETOXY AND LEFT TURN ON TRACK 281.21 TO GENUS AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 170.00 INBOUND. CHART FAS OBST: 1069 TREE 381247N/0842606W DISTANCE TO THLD FROM 200 HAT: 0.55 NM. CHART VDP AT 1.12 MILES TO RW03* *LNAV ONLY. WAAS CHANNEL # 56309 REFERENCE PATH ID: W03A											
UPDEW (IAF)	ZENWA (NOPT) (FB)	118.54 / 5.00	3000												
EPORE (IAF)	ZENWA (NOPT) (FB)	298.66 / 5.00	3000												
ZENWA (IF/IAF)	OKNEW (FB)	028.60 / 6.11	2600												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW ZENWA, RT, 028.60 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>028.63</u> FAF: <u>OKNEW</u> DIST FAF TO MAP: <u>5.06</u> THLD: <u>5.06</u> 4. MIN. ALT: <u>ZENWA 3000, OKNEW 2600, FEMSA/2.00 NM TO RW03 1600*</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>2600</u> GS ALT AT: <u>OKNEW 2600</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>34.0</u> 34:1 IS CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 3W EPOCH YEAR: 1990											
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X										
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1140	3/4	200	1140	3/4	200	1140	3/4	200	1140	3/4	200			
LNAV/VNAV DA	1375	1 1/2	435	1375	1 1/2	435	1375	1 1/2	435	1375	1 1/2	435			
LNAV MDA	1320	1	380	1320	1	380	1320	1	380	1320	1 1/4	380			
CIRCLING	1420	1	473	1420	1	473	1420	1 1/2	473	1580	2	633			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F). CHART NOTE: DME/DME RNP-0.3 NA. *LNAV ONLY CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LEXINGTON ALTIMETER SETTING AND SEE 8260-10															
CITY AND STATE		ELEVATION: 947 TDZE: 940		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:							
GEORGETOWN, KY		AIRPORT NAME:				RNAV (GPS) RWY 3, AMDT 2		AMDT: 1							
		GEORGETOWN SCOTT COUNTY - MARSHALL FLD				29 JUL 2010		DATED 09/25/2008							

QUALITY
2
CHECKED

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

INCREASE LPV DA TO 1178, LNAV/VNAV DA TO 1413, AND ALL MDA 40 FEET; INCREASE LPV AND LNAV/VNAV VISIBILITY ALL CATS AND LNAV CAT C AND CIRCLING CAT D VISIBILITY 1/4 MILE.
CHART NOTE: BARO-VNAV AND VDP NA WITH LEXINGTON ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	299/30 CW 119/30 (NOPT)	299/10 CW 119/10	3100
	299/10 CW 119/10	ZENWA (IF/IAF) (FB)	3000
2.	119/30 CW 209/30	UPDEW (IAF) (FB)	3000
3.	209/30 CW 299/30	EPORE (IAF) (FB)	3000

QUALITY
2
CHECKED

CITY AND STATE

GEORGETOWN, KY

ELEVATION: 947 TDZE: 940

AIRPORT NAME:

GEORGETOWN SCOTT COUNTY - MARSHALL
FLDFACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 3, AMDT 2

29 JUL 2010

SUP:

AMDT: 1

DATED: 09/25/2008

**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	27K
RUNWAY	RW03
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W03A
LTP/FTP LATITUDE	381339.4695N
LTP/FTP LONGITUDE	0842619.7790W
LTP/FTP ELLIPSOIDAL HEIGHT	+02500
FPAP LATITUDE	381459.8700N
FPAP LONGITUDE	0842530.8000W
THRESHOLD CROSSING HEIGHT (TCH)	00034.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

B4BAFF8E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02837
FPAP ORTHOMETRIC HEIGHT	+02837

QUALITY
2
CHECKED

CITY AND STATE
GEORGETOWN, KY

ELEVATION: 947 TDZE: 940
AIRPORT NAME:
GEORGETOWN SCOTT COUNTY - MARSHALL
FLD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 3, AMDT 2

29 JUL 2010

SUP:

AMDT: 1

DATED: 09/25/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 27K K5FR03	AEPORE 010E	POREK5EA0E	A	IF						18000		A JS	
SUSAP 27K K5FR03	AEPORE 020ZENWAK5EA0EE	B	010TF			29870050		+ 03000				A JS	
SUSAP 27K K5FR03	AUPDEW 010UPDEWK5EA0E	A	IF							18000		A JS	
SUSAP 27K K5FR03	AUPDEW 020ZENWAK5EA0EE	B	010TF			11850050		+ 03000				A JS	
SUSAP 27K K5FR03	AZENWA 010ZENWAK5EA0EE	AR	HF			02860040		+ 03000		18000		A JS	
SUSAP 27K K5FR03	R	010ZENWAK5EA0E	I	IF				+ 03000		18000		A JS	
SUSAP 27K K5FR03	R	0200KNEWK5EA1E	F	051TF		02860061		+ 02600				A JS	
SUSAP 27K K5FR03	R	0200KNEWK5EA2WALPV			ALNAV/VNAV	ALNAV						JS	
SUSAP 27K K5FR03	R	021FEMSAK5EA0E	S	031TF		02860031		V 0160001606		-300		A JS	
SUSAP 27K K5FR03	R	030RW03 K5PG0GY	M	031TF		02860020		00965		-300		A JS	
SUSAP 27K K5FR03	R	040	0	M 010CA		0286		+ 01140				A JS	
SUSAP 27K K5FR03	R	050ETOXYK5EA0E		010DF								A JS	
SUSAP 27K K5FR03	R	060GENUSK5EA0EY	L	010TFY		2812		+ 03000				A JS	
SUSAP 27K K5FR03	R	070GENUSK5EA0EE	R	020HM		17000040		+ 03000				A JS	

[illegible]

QUALITY
4
CHECKED

CITY AND STATE GEORGETOWN, KY	ELEVATION: 947 TDZE: 940	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 2 29 JUL 2010	SUP:
	AIRPORT NAME:			AMDT: 1
	GEORGETOWN SCOTT COUNTY - MARSHALL F.L.D.			DATED: 09/25/2008

**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE
GEORGETOWN, KY

ELEVATION: 947 TDZE: 940
AIRPORT NAME:
GEORGETOWN SCOTT COUNTY - MARSHALL
FLD

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 3, AMDT 2
29 JUL 2010

SUP:	
AMDT:	1
DATED:	09/25/2008