

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW13 CLIMB TO 3000 THEN CLIMBING RIGHT TURN TO 4200 DIRECT WHITT AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 047.47 INBOUND. CHART FAS OBST: 2083 TREE 410913N/0752415W. DISTANCE TO THLD FROM 386 HAT: 1.09 NM. CHART VDP AT 1.30 NM TO RW13* *LNAV ONLY. WAAS CHANNEL # 48911 REFERENCE PATH ID: W13A CHART CIRCLING ICON. LTP HAE: 541.9 M					
LVZ VORTAC (IAF)		DEGDE (TF) (FB) (RNP 1.00)		144.20 / 5.30				4200							
VOKYO (IAF)		DEGDE (TF) (FB) (RNP 1.00)		062.01 / 12.95				4200							
DEGDE (IF)		CUTKO (TF) (FB) (RNP 1.00)		128.01 / 6.00				3400							
CUTKO (FAF)		RW13 (MAP) (TF) (FO) (RNP 0.30)		128.09 / 4.63											
RW13 (MAP)		3000 MSL (CA)		128.09				3000							
3000 MSL		WHITT (DF) (FO) (RNP 1.00)						4200							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT DEGDE _____ 3. FAC: 128.09 FAF: CUTKO _____ DIST FAF TO MAP: 4.63 THLD: 4.63 4. MIN. ALT: DEGDE 4200, CUTKO 3400 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3400 GS ALT AT: CUTKO 3400 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 20:1 IS CLEAR 34:1 IS NOT CLEAR 8. MSA FROM: RW13 4000										MAG VAR: 13W EPOCH YEAR: 2005					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	2271	1 1/4	386	2271	1 1/4	386	2271	1 1/4	386	2271	1 1/4	386			
LNAV/VNAV DA	2358	1 1/2	473	2358	1 1/2	473	2358	1 1/2	473	2358	1 1/2	473			
LNAV MDA	2340	1	455	2340	1	455	2340	1 3/8	455	2340	1 3/8	455			
CIRCLING	2420	1	505	2500	1	585	2600	2	685	2660	2 1/2	745			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 54C (130F). CHART NOTE: BARO-VNAV AND VDP NA WHEN USING WILKES-BARRE/SCRANTON ALTIMETER SETTING. CHART NOTE: RWY 13 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. (CONTINUED ON PAGE 2)															
CITY AND STATE MOUNT POCONO, PA		ELEVATION: 1915 TDZE: 1885 AIRPORT NAME: POCONO MOUNTAINS MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, AMDT 3C 24 MAY 2018						SUP:			
												AMDT: 3B			
												DATED 12/11/2014			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON LVZ VORTAC AIRWAY RADIALS 094 CW 212.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WILKES-BARRE/SCRANTON ALTIMETER SETTING:

INCREASE LPV DA TO 2450 FEET, LNAV/VNAV DA TO 2537 FEET AND ALL VISIBILITIES 1/2 SM; INCREASE ALL

MDAS 180 FEET AND VISIBILITY LNAV CAT C/D 3/8 SM AND CIRCLING CAT C/D 1/2 SM.

CHART PLANVIEW NOTE: RADAR REQUIRED FOR PROCEDURE ENTRY AT VOYKO.

CHART NOTE: CIRCLING RWY 23 NA AT NIGHT.

QUALITY
29
CHECKED

CITY AND STATE MOUNT POCONO, PA	ELEVATION: 1915 TDZE: 1885 AIRPORT NAME: POCONO MOUNTAINS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, AMDT 3C 24 MAY 2018	SUP:
				AMDT: 3B
				DATED: 12/11/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KMPO
RUNWAY	RW13
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W13A
LTP/FTP LATITUDE	410821.9480N
LTP/FTP LONGITUDE	0752320.0225W
LTP/FTP ELLIPSOIDAL HEIGHT	+05419
FPAP LATITUDE	410744.0500N
FPAP LONGITUDE	0752133.2900W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1376
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

<u>CRC REMAINDER</u>	B66BEFCD
----------------------	----------

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+05743
FPAP ORTHOMETRIC HEIGHT	+05743

QUALITY
29
CHECKED

CITY AND STATE MOUNT POCONO, PA	ELEVATION: 1915 AIRPORT NAME: POCONO MOUNTAINS MUNI	TDZE: 1885 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, AMDT 3C 24 MAY 2018	SUP:
				AMDT: 3B
				DATED: 12/11/2014