

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES											MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW36R CLIMB TO 500 THEN CLIMBING LEFT TURN TO 3000 DIRECT DNMOR AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000. ADDITIONAL FLIGHT DATA: HOLD W, RT, 069.70 INBOUND. FAS OBST: 280 AAO 282116N/0811949W CHART: 363 TOWER 282030N/0812029W CHART IN PLANVIEW: EXECUTIVE AIRPORT DISTANCE TO THLD FROM 200 HAT: 0.45 NM. CHART VDP AT 1.18 NM TO RW36R* *LNAV ONLY. WAAS CHANNEL # 40212 REFERENCE PATH ID: W36A CHART CIRCLING ICON LTP HAE: -.2 M							
MINEE		BOYAB (TF) (FB) (RNP 2.00)			091.25 / 14.78			4000									
BOYAB (IAF)		FLOZY (NOPT) (TF) (FB) (RNP 1.00)			066.34 / 8.96			4000									
FLOZY (IF/IAF)		SILKY (TF) (FB) (RNP 1.00)			005.46 / 3.15			3000									
SILKY		JAKOR (TF) (FB) (RNP 1.00)			005.46 / 4.42			1600									
JAKOR (FAF)		RW36R (MAP) (TF) (FO) (RNP 0.30)			005.46 / 4.56												
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S FLOZY, LT, 005.46 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: 005.46 FAF: JAKOR DIST FAF TO MAP: 4.56 THLD: 4.56 4. MIN. ALT: FLOZY 4000, SILKY 3000, JAKOR 1600 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: JAKOR 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 56.3 34:1 IS CLEAR 8. MSA FROM: RW36R 3000																	
											MAG VAR: 6W					EPOCH YEAR: 2015	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD								
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	292	1800	200	292	1800	200	292	1800	200	292	1800	200					
LNAV/VNAV DA	454	4000	362	454	4000	362	454	4000	362	454	4000	362					
LNAV MDA	540	2400	448	540	2400	448	540	4500	448	540	4500	448					
CIRCLING	740	1	644	740	1	644	740	1 3/4	644	740	2	644					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -1C (31F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. (CONTINUED ON PAGE 2)																	
CITY AND STATE ORLANDO, FL				ELEVATION: 96 TDZE: 92 AIRPORT NAME: ORLANDO INTL				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36R, AMDT 2 12 OCTOBER 2017				SUP: AMDT: 1 DATED 02/05/2015			



**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW36R (MAP)	500 MSL (CA)	005.46	500
500 MSL	DNMOR (DF) (FO)		3000

NOTES, (CONT.):

CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS.

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO RVR 6000.

QUALITY
23
CHECKED

CITY AND STATE

ORLANDO, FL

ELEVATION: 96

TDZE: 92

AIRPORT NAME:

ORLANDO INTL

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36R, AMDT 2

12 OCTOBER 2017

SUP:

AMDT: 1

DATED: 02/05/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KMCO
RUNWAY	RW36R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	282455.1465N
LTP/FTP LONGITUDE	0811919.0355W
LTP/FTP ELLIPSOIDAL HEIGHT	-00002
FPAP LATITUDE	282654.0035N
FPAP LONGITUDE	0811920.3020W
THRESHOLD CROSSING HEIGHT (TCH)	00056.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 EB017B74

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00277
FPAP ORTHOMETRIC HEIGHT	+00277

QUALITY
23
CHECKED

CITY AND STATE ORLANDO, FL	ELEVATION: 96 TDZE: 92 AIRPORT NAME: ORLANDO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36R, AMDT 2 12 OCTOBER 2017	SUP:
				AMDT: 1
				DATED: 02/05/2015