

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**NDB STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: AAF NDB
TERES INT	AAF NDB	253.46 / 38.30	2100	<p><b>CLIMB TO 1300 THEN CLIMBING RIGHT TURN TO 2100 DIRECT AAF NDB AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2100.</b></p> <p>ADDITIONAL FLIGHT DATA:  <b>HOLD NW, RT, 145.83 INBOUND.</b>  <b>FAS OBST: 215 AAO 294823N/0850424W.</b>  <b>CHART W-151B, W-470A, TYNDALL E, F, G MOAS.</b>  <b>FAC CROSSES RWY C/L EXTENDED 3003 FT FROM THLD.</b>  <b>CHART PLANVIEW NOTE: RADAR REQUIRED.</b></p>

1. PT L SIDE OF COURSE 325.83 OUTBOUND 2100 FT WITHIN 10 MILES OF AAF NDB (IAF)  
2. \_\_\_\_\_  
3. FAC 145.83 FAF \_\_\_\_\_ DIST FAF TO MAP \_\_\_\_\_ THLD \_\_\_\_\_  
4. MIN. ALT \_\_\_\_\_  
8. MSA FROM: **AAF NDB 2100**

MAG VAR: **3W** EPOCH YEAR: **2010**

**MINIMUMS**

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
<b>S-14</b>	<b>580</b>	<b>1</b>	<b>560</b>	<b>580</b>	<b>1</b>	<b>560</b>	<b>580</b>	<b>1 3/4</b>	<b>560</b>	<b>580</b>	<b>1 3/4</b>	<b>560</b>			
<b>CIRCLING</b>	<b>600</b>	<b>1</b>	<b>580</b>	<b>600</b>	<b>1</b>	<b>580</b>	<b>600</b>	<b>1 3/4</b>	<b>580</b>	<b>600</b>	<b>2 1/4</b>	<b>580</b>			

NOTES:  
**CHART NOTE: RWY 14 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.**  
**CHART NOTE: STRAIGHT-IN RWY 14 NA AT NIGHT, CIRCLING RWY 6, 18, 36 NA AT NIGHT.**  
**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED; USE NORTHWEST FLORIDA BEACHES INTL ALTIMETER. SETTING AND INCREASE ALL MDA 140 FEET, INCREASE S-14 AND CIRCLING CAT C/D VISIBILITY 1/4 MILE.**



CITY AND STATE <b>APALACHICOLA, FL</b>	ELEVATION: <b>20</b> TDZE: <b>20</b>	FACILITY IDENTIFIER: <b>AAF</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>NDB RWY 14, AMDT 2C</b> <b>29 MARCH 2018</b>	SUP
	AIRPORT NAME: <b>APALACHICOLA RGNL-CLEVE RANDOLPH FIELD</b>			AMDT <b>2B</b>
				DATE <b>08/20/2015</b>