

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW32 LNAV: RW32
CEW VORTAC	MEMSE (TF) (FB) (RNP 1.00)	146.43 / 37.04	2000	CLIMBING LEFT TURN TO 2000 DIRECT AJLIP AND HOLD.
MEMSE (IAF)	AJLIP (NOPT) (TF) (FB) (RNP 1.00)	225.61 / 5.04	2000	
AJLIP (IF/IAF)	UFEBA (TF) (FB) (RNP 1.00)	323.20 / 5.67	1600	ADDITIONAL FLIGHT DATA: CHART FAS OBST: 176 VERTICAL_STRUCTURE 302305N/0862721W CHART FAS OBST: 207 BUILDING 302305N/0862800W CHART R-2919A. CHART R-2919B. CHART W-151A. CHART VDP AT 1.18 NM TO RW32. WAAS CHANNEL # 56623 REFERENCE PATH ID: W32A CHART CIRCLING ICON. UFEBA TO RW32: 3.00/42. CHART: EGLIN AFB LTP HAE: -20.8 M
UFEBA (FAF)	RW32 (MAP) (TF) (FO) (RNP 0.30)	323.17 / 4.83		
RW32 (MAP)	422 MSL (CA)	323.17		
422 MSL	AJLIP (DF) (FO) (RNP 1.00)		2000	

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD SE AJLIP, RT, 323.20 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
3. FAC: 323.17 FAF: UFEBA DIST FAF TO MAP: 4.83 THLD: 4.83
4. MIN. ALT: AJLIP 2000, UFEBA 1600
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
7. GS ANGLE:        TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW32 1800

MAG VAR: **1W** EPOCH YEAR: **2000**

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	440	1	420	440	1	420	440	1 1/8	420	440	1 1/8	420			
LNAV MDA	540	1	520	540	1	520	540	1 3/8	520	540	1 3/8	520			
CIRCLING	580	1	558	580	1	558	680	1 3/4	658	680	2	658			

NOTES:  
 CHART NOTE: RWY 32 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: VDP NA WHEN USING CRESTVIEW ALTIMETER SETTING.  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CRESTVIEW ALTIMETER SETTING AND INCREASE  
 (CONTINUED ON PAGE 2)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE <b>DESTIN, FL</b>	ELEVATION: <b>22</b> TDZE: <b>20</b> AIRPORT NAME: <b>DESTIN EXECUTIVE</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 32, AMDT 1C</b> 7 DECEMBER 2017	SUP: AMDT: <b>1B</b> DATED <b>05/28/2015</b>
-------------------------------------	--	-------------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):**  
**ALL MDA 80 FEET; INCREASE LP CATS C AND D VISIBILITY 1/4 SM, INCREASE LNAV CATS C AND D VISIBILITY 3/8 SM, AND INCREASE CIRCLING CAT C VISIBILITY 1/4 SM.**  
**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON CEV VORTAC AIRWAY RADIALS 073 CW 088.**



CITY AND STATE <b>DESTIN, FL</b>	ELEVATION: 22 AIRPORT NAME: <b>DESTIN EXECUTIVE</b>	TDZE: 20	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 32, AMDT 1C</b> 7 DECEMBER 2017	SUP:
					AMDT: <b>1B</b>
					DATED: <b>05/28/2015</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KDTS
RUNWAY	RW32
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W32A
LTP/FTP LATITUDE	302340.6580N
LTP/FTP LONGITUDE	0862759.7780W
LTP/FTP ELLIPSOIDAL HEIGHT	-00208
FPAP LATITUDE	302451.1700N
FPAP LONGITUDE	0862903.0200W
THRESHOLD CROSSING HEIGHT (TCH)	00042.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

**CRC REMAINDER** 7ED04C61

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00062
FPAP ORTHOMETRIC HEIGHT	+00062



CITY AND STATE <b>DESTIN, FL</b>	<b>ELEVATION: 22</b>	<b>TDZE: 20</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 32, AMDT 1C</b> 7 DECEMBER 2017	SUP:
	AIRPORT NAME: <b>DESTIN EXECUTIVE</b>				AMDT: <b>1B</b>
					DATED: <b>05/28/2015</b>