12/11/2017

FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE

GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAM	<u>//E</u>					NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
UYRIG						FIVE	UYRIG5.UYRIG	FOUR	07/21/2016	1 FEB 2018
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV					
			\boxtimes		\boxtimes					

DP ROUTE DESCRIPTION:

TAKE-OFF RWY 8: CLIMB HEADING 078.44 TO INTERCEPT COURSE 063.60 TO TALJE, THEN ON TRACK 089.79 TO UYRIG, THENCE

...ON TRANSITION OR ASSIGNED ROUTE. MAINTAIN 14,000, EXPECT CLEARANCE TO ASSIGNED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	TRANSITION COMPUTER CODE	<u>FROM</u> <u>FIX/NAVAID</u>	<u>TO</u> <u>FIX/NAVAID</u>	COURSE	DISTANCE	MEA	MOCA	CROSSING ALTITUDE/FIXES
SNOW	UYRIG5.SXW	UYRIG	SXW VOR/DME	055.60	13.80	11700		
RED TABLE	UYRIG5.DBL	UYRIG	DBL VOR/DME	098.39	18.01	14000		

PROCEDURAL DATA NOTES:

NOTE: RNAV 1

NOTE: GPS REQUIRED

TAKEOFF MINIMUMS:

RWY 26: NA - ATC.

RWY 8: STANDARD WITH MINIMUM CLIMB OF 335 FEET PER NM TO 10000.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 8: TERRAIN BEGINNING 155 FT FROM DER, 380 FT RIGHT OF CENTERLINE, UP TO 5551 FT MSL. POLE 4049 FT FROM DER, 1379 FT RIGHT OF CENTERLINE, 42 FT AGL/5642 FT MSL. OL ON NDB TOWER 41 FT FROM DER, 300 FT LEFT OF CENTERLINE, 46 FT AGL/5586 FT MSL.

CONTROLLING OBSTACLES:

RWY 8: 8545 FT MSL AAO, 393624.00N/1072930.98W (CLIMB GRADIENT), 8999 FT MSL AAO, 393522.30N/1072403.17W (CLIMB TO ALTITUDE).

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KRIL 10E EPOCH YEAR:2010 DME/DME ASSESSMENT: NOT CONDUCTED CHART: TOP ALTITUDE: 14000

AIRPORTS SERVED:

AIRPORTS SERVED:		NAL/>		
AIRPORT NAME	CITY	00	STATE	
RIFLE GARFIELD COUNTY	RIFLE	CHECKER	СО	

12/11/2017

FEDERAL AVIATION ADMINISTRATION

FLIGHT STANDARDS SERVICE

GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
UYRIG	FIVE	UYRIG5.UYRIG	FOUR	07/21/2016	1 FEB 2018
COMMUNICATIONS:					

DEP CON

FIXES AND/OR NAVAIDS:

REMARKS:

<u>Flight ins</u> f Flight insf			OFFICE SYMBOL:	DATE:	<i>Digitally signed by</i> <i>ALLAN WILL</i> Dec 06, 2017				
DEVELOPED	<u>D BY</u> :	Digitally	signed by				OFFICE SYMBOL:	DATE:	
BETTY F. RIC	CHARDS	BETTY F	RICHARDS				AJV-5412	11/20/2017	,
		Nov 2), 2017						
APPROVED	BY:	L	Digitally signed	l by			OFFICE SYMBOL:	DATE:	
GEORGE DA	AVIS		ALLAN WIL	L			AJV-5410		
<u>Required e</u> Routine	EFFECTIV	<u>E DATE</u> :	Dec 05, 201	7					
COORDINAT	TED WITH:	:							
<u>A4A</u>	<u>ALPA</u>	AOPA	APA	HAI	NBAA				
	\boxtimes	\boxtimes			\boxtimes				

OTHER:

ZDV, CO AERO, AMGR

CHANGES - REASONS:

1. AIRPORT NAME CHANGED FROM GARFIELD COUNTY RGNL TO RIFLE GARFIELD COUNTY - PER FPT AND AMGR REQUEST.

2. SNOW TRANSITION DISTANCE CHANGED FROM 13.81 TO 13.80 BASED ON UPDATED LAT/LONGS OF THE SXW VOR/DME.

NFDD No. 237

12/11/2017

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE **DEPARTURE (DATA RECORD)**

DEPARTORE (DATA RECORD)											
DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
UYRIG							FIVE	UYRIG5.UYRIG	FOUR	07/21/2016	1 FEB 2018
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FB	LEG TYPE	<u>TC</u>	<u>DIST</u> (NM)	ALTITUI	DE <u>SPEED</u>		REMARKS	
RWY 08 (AER)	393134.85N/1074425.39W	Ν	-	-	-	-			CG 335 FT/NM TO 10000		
	393140.02N/1074016.56W	-	-	VI	088.44	3.21			RECOMMENDED NAVAID:	RIL VOR/DME	
TALJE	393400.04N/1072959.93W	Y	FB	CF	073.60	8.28					
UYRIG	393204.85N/1071544.42W	Y	FB	TF	099.79	11.19					
UYRIG	393204.85N/1071544.42W	Y	-	IF	-	-			UYRIG5.SXW		
SXW VOR/DME	393746.12N/1065928.21W	Y	FB	TF	065.60	13.80					
UYRIG	393204.85N/1071544.42W	Y	-	IF	-	-			UYRIG5.DBL		
DBL VOR/DME	392621.64N/1065340.85W	Y	FB	TF	108.39	18.01					