

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.						
TERMINAL ROUTES														MISSED APPROACH									
FROM				TO			COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW13 CLIMB TO 3000 DIRECT WEDBU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 311.47 INBOUND. FAS OBST: 440 AAO 282505N/0974345W 475 AAO 282605N/0974415W. CHART KINGSVILLE 4 MOA. WAAS CHANNEL # 70740 REFERENCE PATH ID: W13A CHART CIRCLING ICON. DISTANCE TO THLD FROM 250 HAT: 0.64 NM. CHART BEEVILLE MUNI AWOS-3. LTP HAE: 28.3 M MAG VAR: 4E EPOCH YEAR: 2015										
INAH (IF/IAF)				ZEVUT (TF) (FB) (RNP 1.00)			131.32 / 6.02				1800												
ZEVUT (FAF)				RW13 (MAP) (TF) (FO) (RNP 0.30)			131.36 / 4.92																
RW13 (MAP)				434 MSL (CA)			131.36				3000												
434 MSL				WEDBU (DF) (FO) (RNP 1.00)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																							
2. HOLD NW INAH, RT, 131.32 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																							
3. FAC: 131.36 FAF: _____ DIST FAF TO MAP: 4.92 THLD: 4.92																							
4. MIN. ALT: INAH 3000, ZEVUT 1800																							
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																							
6. MIN GS INCPT: 1800 GS ALT AT: ZEVUT 1800 OM: _____ MM: _____ IM: _____																							
7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR																							
8. MSA FROM: _____																							
MINIMUMS																							
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A X																
CATEGORY =====>		A			B			C			D			E									
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA								
LPV DA	434	3/4	250	434	3/4	250	434	3/4	250	434	3/4	250											
LNAV/VNAV DA	586	1 3/8	402	586	1 3/8	402	586	1 3/8	402	586	1 3/8	402											
LNAV MDA	720	1	536	720	1	536	720	1 1/2	536	720	1 1/2	536											
CIRCLING	720	1	536	720	1	536	720	1 1/2	536	920	2 1/4	736											
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: DME/DME RNP-0.3 NA.																							
CITY AND STATE BEEVILLE, TX				ELEVATION: 184 TDZE: 184 AIRPORT NAME: CHASE FIELD INDUSTRIAL			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 17 AUGUST 2017					SUP: AMDT: NONE DATED									

QUALITY
25
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	041/30 CW 221/30 (NOPT)	INAH1 (IF/IAF) (FB)	3000
2.	221/30 CW 041/30	INAH1 (IF/IAF) (FO)	3000

QUALITY
25
CHECKED

CITY AND STATE

BEEVILLE, TX

ELEVATION: 184

TDZE: 184

AIRPORT NAME:

CHASE FIELD INDUSTRIAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, ORIG

17 AUGUST 2017

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	TX2
RUNWAY	RW13
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W13A
LTP/FTP LATITUDE	282213.0170N
LTP/FTP LONGITUDE	0974014.3855W
LTP/FTP ELLIPSOIDAL HEIGHT	+00283
FPAP LATITUDE	282109.4115N
FPAP LONGITUDE	0973903.4665W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0312
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

4A2A5F22

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00554
FPAP ORTHOMETRIC HEIGHT	+00554

QUALITY
25
CHECKED

CITY AND STATE

BEEVILLE, TX

ELEVATION: 184

TDZE: 184

AIRPORT NAME:

CHASE FIELD INDUSTRIAL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 13, ORIG

17 AUGUST 2017

SUP:

AMDT:

NONE

DATED: