

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
TEDDD	FIVE	TEDDD5.TEDDD	FOUR	08/17/2017	19 JULY 2018

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	☐	☐	☒	☐	☒

DP ROUTE DESCRIPTION:**TAKEOFF RWY 6:** CLIMB HEADING 063.81 TO 1120, THEN AS ASSIGNED BY ATC, EXPECT RADAR VECTORS TO TEDDD. THENCE...**TAKEOFF RWY 24:** CLIMB HEADING 243.83 TO 1120, THEN AS ASSIGNED BY ATC, EXPECT RADAR VECTORS TO TEDDD. THENCE...**TAKEOFF RWY 11:** CLIMB HEADING 123.17 TO 1120, THEN LEFT TURN DIRECT FUNKE, CROSS FUNKE AT OR ABOVE 2500, THEN ON DEPICTED ROUTE TO TEDDD. THENCE...**TAKEOFF RWY 12L, 12R:** CLIMB HEADING 123.19 TO 1120, THEN LEFT TURN DIRECT FUNKE, CROSS FUNKE AT OR ABOVE 2500, THEN ON DEPICTED ROUTE TO TEDDD. THENCE...**TAKEOFF RWY 29:** CLIMB HEADING 303.18 TO 1120, THEN RIGHT TURN DIRECT DSAPP, CROSS DSAPP AT OR ABOVE 2500, THEN ON DEPICTED ROUTE TO TEDDD. THENCE...**TAKEOFF RWY 30L:** CLIMB HEADING 303.20 TO 1120, THEN RIGHT TURN DIRECT WOLTR, CROSS WOLTR AT OR ABOVE 2500, THEN ON DEPICTED ROUTE TO TEDDD. THENCE...**TAKEOFF RWY 30R:** CLIMB HEADING 303.21 TO 1120, THEN RIGHT TURN DIRECT WOLTR, CROSS WOLTR AT OR ABOVE 2500, THEN ON DEPICTED ROUTE TO TEDDD. THENCE...

... (TRANSITION). MAINTAIN 5000, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
HILTS	TEDDD5.HILTS	TEDDD	ENL VORTAC	TRACK 110.49	20.81	13600	2000	
			ZOLLI	TRACK 114.60	14.91	16600	2100	
			HILTS	TRACK 114.78	28.17	FL180	2000	
LOUISVILLE	TEDDD5.IIU	TEDDD	ENL VORTAC	TRACK 110.49	20.81	13600	2000	
			ZOLLI	TRACK 114.60	14.91	16600	2100	
			HILTS	TRACK 114.78	28.17	FL180	2000	
			IIU VORTAC	TRACK 090.83	130.11	FL180	2400	

PROCEDURAL DATA NOTES:**NOTE:** RNAV 1.**NOTE:** DME/DME/IRU OR GPS REQUIRED.**NOTE:** RADAR REQUIRED.**NOTE:** FOR USE BY TURBOJET AIRCRAFT ONLY.**TAKEOFF MINIMUMS:****RWY 6, 24:** STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1120 THEN MINIMUM CLIMB OF 280 FT PER NM TO 5000.**RWY 11, 12L, 12R:** STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO FUNKE.**RWY 29:** STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO DSAPP.**RWY 30L, 30R:** STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO WOLTR.

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
TEDDD	FIVE	TEDDD5.TEDDD	FOUR	08/17/2017	19 JULY 2018

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**LOST COMMUNICATIONS PROCEDURES:****ADDITIONAL FLIGHT DATA:**

REFERENCE MAG VAR: KSTL 1W, EPOCH YEAR: 2020

DME/DME ASSESSMENT: SAT (RNP 2.0)

CHART: TOP ALTITUDE: 5000**PILOT NAVIGATION AREA:**

7 NM ARC CENTERED ON TEDDD (IF), CW

FROM: POINT A (BEARING 065 DEGREES TO TEDDD)

TO: POINT B (BEARING 155 DEGREES TO TEDDD)

MINIMUM ALTITUDE - 10000

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
ST LOUIS LAMBERT INTL	ST LOUIS	MO

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, GND METER, DEP CON, TOWER

FIXES AND/OR NAVAIDS:

ANNII, LENXX, KAEYE, RAMKR



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
TEDDD	FIVE	TEDDD5.TEDDD	FOUR	08/17/2017	19 JULY 2018

REMARKS:

ABBREVIATED AMENDMENT, SPEED RESTRICTION "ACCELERATE TO 250 KIAS; IF UNABLE, ADVISE ATC" DELETED.
ABBREVIATED AMENDMENT, DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS.
TEDDD THREE WAS ALSO AN ABBREVIATED AMENDMENT. FLIGHT CHECK MAPS AND RNAV PRO EVALUATIONS FROM TEDDD TWO USED IN "S" AND "P" FILES.

FLIGHT INSPECTED BY:**OFFICE SYMBOL:****DATE:**

FLIGHT INSPECTION REVIEW NOT REQUIRED - PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-333) MEMO,
DEC 22,2017.

DEVELOPED BY:**OFFICE SYMBOL:****DATE:**

LONNIE EVERHART
(EDUARDO LIMA)

AJV-5400

04/26/2018

APPROVED BY:**OFFICE SYMBOL:****DATE:**

LONNIE EVERHART

AJV-5400

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:**A4A****ALPA****AOPA****APA****HAI****NBAA****OTHER:**

ZKC, STL APP CON, STL ATCT, AMGR

CHANGES - REASONS:

SPEED RESTRICTION NOTE "ACCELERATE TO 250 KIAS; IF UNABLE, ADVISE ATC" DELETED.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
TEDDD							FIVE	TEDDD5.TEDDD	FOUR	08/17/2017	19 JULY 2018
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS	
RW06 (AER)	384448.04N/0902252.43W	N	-	-	-	-					
1120 MSL		-	-	VA	062.81	-				CG 500 FT/NM TO 1120	
		-	-	VM	062.81	-				CG 280 FT/NM TO 5000	
TEDDD	383211.84N/0893430.31W	Y	FB	DF	-	-					
RW11 (AER)	384535.83N/0902435.55W	N	-	-	-	-					
1120 MSL		-	-	VA	122.17	-				CG 500 FT/NM TO FUNKE	
FUNKE	384339.26N/0901535.58W	Y	FB	DF	-	-	AT/ABOVE 2500			LEFT TURN	
RAMKR	384337.54N/0901136.78W	Y	FB	TF	090.51	3.11					
TEDDD	383211.84N/0893430.31W	Y	FB	TF	111.24	31.24					
RW12L (AER)	384506.41N/0902158.66W	N	-	-	-	-					
1120 MSL		-	-	VA	122.19	-				CG 500 FT/NM TO FUNKE	
FUNKE	384339.26N/0901535.58W	Y	FB	DF	-	-	AT/ABOVE 2500			LEFT TURN	
RAMKR	384337.54N/0901136.78W	Y	FB	TF	090.51	3.11					
TEDDD	383211.84N/0893430.31W	Y	FB	TF	111.24	31.24					
RW12R (AER)*	384511.59N/0902239.98W*	N	-	-	-	-				*DISPL THLD (467)	
1120 MSL		-	-	VA	122.19	-				CG 500 FT/NM TO FUNKE	
FUNKE	384339.26N/0901535.58W	Y	FB	DF	-	-	AT/ABOVE 2500			LEFT TURN	
RAMKR	384337.54N/0901136.78W	Y	FB	TF	090.51	3.11					
TEDDD	383211.84N/0893430.31W	Y	FB	TF	111.24	31.24					

QUALITY

4

QUALITY
4
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
TEDDD		FIVE		TEDDD5.TEDDD		FOUR		08/17/2017	19 JULY 2018
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW24 (AER)	384522.38N/0902127.02W	N	-	-	-	-			
1120 MSL		-	-	VA	242.83	-			CG 500 FT/NM TO 1120
		-	-	VM	242.83	-			CG 280 FT/NM TO 5000
TEDDD	383211.84N/0893430.31W	Y	FB	DF	-	-			
RW29 (AER)	384448.46N/0902259.39W	N	-	-	-	-			
1120 MSL		-	-	VA	302.18	-			CG 500 FT/NM TO DSAPP
DSAPP	385001.06N/0902638.98W	Y	FB	DF	-	-	AT/ABOVE 2500		RIGHT TURN
ANNII	385252.69N/0902322.37W	Y	FB	TF	041.83	3.84			
LENXX	385404.00N/0901846.99W	Y	FB	TF	071.64	3.78			
KAEYE	385323.93N/0901343.89W	Y	FB	TF	099.58	4.00			
TEDDD	383211.84N/0893430.31W	Y	FB	TF	124.40	37.30			
RW30L (AER)*	384417.08N/0902049.42W*	N	-	-	-	-			*DISPL THLD (201)
1120 MSL		-	-	VA	302.20	-			CG 500 FT/NM TO WOLTR
WOLTR	384941.32N/0902503.02W	Y	FB	DF	-	-	AT/ABOVE 2500		RIGHT TURN
ANNII	385252.69N/0902322.37W	Y	FB	TF	022.35	3.45			
LENXX	385404.00N/0901846.99W	Y	FB	TF	071.64	3.78			
KAEYE	385323.93N/0901343.89W	Y	FB	TF	099.58	4.00			
TEDDD	383211.84N/0893430.31W	Y	FB	TF	124.40	37.30			

QUALITY
4
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE			
TEDDD		FIVE	TEDDD5.TEDDD	FOUR	08/17/2017	19 JULY 2018			
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW30R (AER)	384418.99N/0902022.51W	N	-	-	-	-			
1120 MSL		-	-	VA	302.21	-			CG 500 FT/NM TO WOLTR
WOLTR	384941.32N/0902503.02W	Y	FB	DF	-	-	AT/ABOVE 2500		RIGHT TURN
ANNII	385252.69N/0902322.37W	Y	FB	TF	022.35	3.45			
LENXX	385404.00N/0901846.99W	Y	FB	TF	071.64	3.78			
KAEYE	385323.93N/0901343.89W	Y	FB	TF	099.58	4.00			
TEDDD	383211.84N/0893430.31W	Y	FB	TF	124.40	37.30			
TEDDD	383211.84N/0893430.31W	Y	-	IF	-	-			TEDDD5.HILTS
ENL VORTAC	382512.00N/0890932.39W	Y	FB	TF	109.49	20.81			
ZOLLI	381912.23N/0885210.73W	Y	FB	TF	113.60	14.91			
HILTS	380745.42N/0881930.79W	T	FB	TF	113.78	28.17			
TEDDD	383211.84N/0893430.31W	Y	-	IF	-	-			TEDDD5.IIU
ENL VORTAC	382512.00N/0890932.39W	Y	FB	TF	109.49	20.81			
ZOLLI	381912.23N/0885210.73W	Y	FB	TF	113.60	14.91			
HILTS	380745.42N/0881930.79W	Y	FB	TF	113.78	28.17			
IIU VORTAC	380612.47N/0853438.77W	Y	FB	TF	089.83	130.11			

QUALITY
4
CHECKED