

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
JOT VOR/DME (IAF)	UYELO (NOPT) (TF) (FB) (RNP 1.00)	092.67 / 24.98	2400	LNAV: RW09
EON VORTAC (IAF)	UYELO (NOPT) (TF) (FB) (RNP 1.00)	006.29 / 16.27	2400	CLIMBING RIGHT TURN TO 2400 DIRECT UYELO AND HOLD.
UYELO (IF/IAF)	HEFER (TF) (FB) (RNP 1.00)	092.02 / 5.10	2300	
HEFER (FAF)	KOGEK/2.10 NM TO RW09 (TF) (FB) (RNP 0.30)	092.10 / 2.99		
KOGEK/2.10 NM TO RW09 (SEE FORM 8260-10)	RW09 (MAP) (TF) (FO) (RNP 0.30)	092.10 / 2.10		ADDITIONAL FLIGHT DATA: CHART FAS OBST: 780 TOWER 413203N/0873450W. CHART 951 TOWER 413223N/0873740W. HEFER TO RW09: 3.04/40.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD W UYELO, RT, 092.02 INBOUND, 2400 FT. IN LIEU OF PT (IAF)
3. FAC: 092.10 FAF: HEFER DIST FAF TO MAP: 5.09 THLD: 5.09
4. MIN. ALT: UYELO 2400, HEFER 2300, KOGEK/2.10 NM TO RW09 1320
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 20:1 IS NOT CLEAR 34:1 IS NOT CLEAR
8. MSA FROM: RW09 3400

MAG VAR: **2W** EPOCH YEAR: **1995**

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1080	1	463	1080	1	463		NA			NA				
CIRCLING	1140	1	520	1140	1	520		NA			NA				

NOTES:
 CHART NOTE: RWY 9 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT.
 CHART NOTE: RWY 9 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON JOT VOR/DME AIRWAY RADIALS 091 CW 171.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON EON VORTAC AIRWAY RADIALS 279 CW 096.



CITY AND STATE CHICAGO, IL	ELEVATION: 620 TDZE: 617 AIRPORT NAME: LANSING MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, ORIG-B 24 MAY 2018	SUP: AMDT: ORIG-A DATED 03/30/2017
--------------------------------------	--	-------------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW09 (MAP)	1020 MSL (CA)	092.10	
1020 MSL	UYELO (DF) (FO) (RNP 1.00)		2400

QUALITY
10

CHECKED

CITY AND STATE CHICAGO, IL	ELEVATION: 620	TDZE: 617	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, ORIG-B 24 MAY 2018	SUP:
	AIRPORT NAME: LANSING MUNI				AMDT: ORIG-A
					DATED: 03/30/2017