

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
										MISSED APPROACH										
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LP: RW22 LNAV: RW22										
MORAN (IAF)		GEMEH (NOPT) (FB)		274.26 / 9.52				2700		CLIMB TO 2600 DIRECT VUNJU AND HOLD.										
FARLN (IAF)		GEMEH (NOPT) (FB)		165.96 / 18.65				2700												
GEMEH (IF/IAF)		NOCPO (FB)		216.66 / 6.40				2100												
NOCPO (FAF)		RW22 (MAP) (FO)		216.62 / 4.09																
RW22 (MAP)		1158 MSL		216.62						ADDITIONAL FLIGHT DATA: HOLD SW, RT, 036.52 INBOUND. CHART FAS OBST: 1019 TREE 385732N/0814809W CHART FAS OBST: 1240 STACK 385611N/0814935W WAAS CHANNEL # 61323 REFERENCE PATH ID: W22A NOCPO TO RW22: 3.00/40. LTP HAE: 197.1 M										
1158 MSL		VUNJU (FO)						2600												
Previously published in TL 11-16: Changed NOCPO FIX STATE CODE FROM K6o TO K5o FOR ARINC CODING																				
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE GEMEH, RT, 216.66 INBOUND, 2700 FT. IN LIEU OF PT (IAF) 3. FAC: 216.62 FAF: NOCPO DIST FAF TO MAP: 4.09 THLD: 4.09 4. MIN. ALT: GEMEH 2700, NOCPO 2100 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW22 3000														MAG VAR: 7W		EPOCH YEAR: 2000				
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT														ALTERNATE: N A X						
CATEGORY =====>	A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
LP MDA	1280	1	522	1280	1	522	1280	1 1/2	522		NA									
LNAV MDA	1540	1	782	1540	1 1/4	782	1540	2 1/2	782		NA									
CIRCLING	1600	1 1/4	842	1600	1 1/4	842	1600	2 1/2	842		NA									
NOTES:																				
CHART NOTE: DME/DME RNP-0.3 NA.																				
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.																				
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MORAN ON V115 NORTHBOUND.																				
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FARLN ON V133 NORTHBOUND.																				
(SEE FORM 8260-10)																				
CITY AND STATE RAVENSWOOD, WV				ELEVATION: 758 THRE: 758 AIRPORT NAME: JACKSON COUNTY				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 25 AUG 2011				SUP: AMD'T: NONE DATED						

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 22 NA AT NIGHT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE POINT PLEASANT ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE LP AND LNAV CAT C VISIBILITY 1/4 MILE.

CITY AND STATE

RAVENSWOOD, WV

ELEVATION: 758

THRE: 758

AIRPORT NAME:

JACKSON COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 22, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER I18
RUNWAY RW22
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W22A
LTP/FTP LATITUDE 385604.3575N
LTP/FTP LONGITUDE 0814857.6375W
LTP/FTP ELLIPSOIDAL HEIGHT +01971
FPAP LATITUDE 385446.8000N
FPAP LONGITUDE 0814954.0100W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1528
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

1EDF88E9

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +02311
FPAP ORTHOMETRIC HEIGHT +02311

CITY AND STATE

RAVENSWOOD, WV

ELEVATION: 758

THRE: 758

AIRPORT NAME:

JACKSON COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 22, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE RAVENSWOOD, WV	ELEVATION: 758 THRE: 758 AIRPORT NAME: JACKSON COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 25 AUG 2011	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP I18 K6PR22 RW22 002E +02311+02311LP 61323

[illegible]

SUSAP I18 K6SRW22 K6PG

0 18018003025

M

CITY AND STATE
RAVENSWOOD, WV

ELEVATION: 758 THRE: 758
AIRPORT NAME:
JACKSON COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, ORIG
25 AUG 2011

SUP:	
AMDT:	NONE
DATED:	

QUALITY
6
CHECKED