

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VDP NA WITH SEYMOUR JOHNSON AFB ALTIMETER SETTING.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SEYMOUR JOHNSON AFB ALTIMETER SETTING AND INCREASE LPV DA TO 432, LNAV/VNAV DA TO 413, AND ALL MDA 60 FEET. INCREASE LPV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/8 MILE, AND INCREASE LNAV/VNAV ALL CATS AND CIRCLING CAT D VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	140/30 CW 320/30 (NOPT)	WINTI (IF/IAF) (FB)	2500
2.	320/30 CW 140/30	320/5 CW 140/5	3100
3.	320/5 CW 140/5	WINTI (IF/IAF) (FO)	2500

QUALITY
CHECKED

CITY AND STATE KINSTON, NC	ELEVATION: 93 THRE: 86 AIRPORT NAME: KINSTON RGNL JETPORT AT STALLINGS FLD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, AMDT 3 29 MAY 2014	SUP:
				AMDT: 2
				DATED: 10/25/2007

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KISO
RUNWAY	RW23
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W23A
LTP/FTP LATITUDE	352036.0095N
LTP/FTP LONGITUDE	0773546.1615W
LTP/FTP ELLIPSOIDAL HEIGHT	-00095
FPAP LATITUDE	351910.2915N
FPAP LONGITUDE	0773717.4115W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

3AE9BC47

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00262
FPAP ORTHOMETRIC HEIGHT	+00262

QUALITY
8
CHECKED

CITY AND STATE

KINSTON, NC

ELEVATION: 93

THRE: 86

AIRPORT NAME:

KINSTON RGNL JETPORT AT STALLINGS FLD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 23, AMDT 3
29 MAY 2014

SUP:

AMDT:

2

DATED:

10/25/2007

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KISOK7FR23	AWINTI	010WINTIK7EA0EE	AR	HF			23020050	+	02500	18000		A	JS
SUSAP KISOK7FR23	R	010WINTIK7EA0E	I	IF				+	02500	18000		A	JS
SUSAP KISOK7FR23	R	020HUKORK7EA1E	F	051TF			23020070	+	01700			A	JS
SUSAP KISOK7FR23	R	020HUKORK7EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KISOK7FR23	R	021WOVTAK7EA0E	S	031TF			23020023	V	0092000964	-300		A	JS
SUSAP KISOK7FR23	R	030RW23	K7PG0GY	M	031TF		23020026		00136	-300		A	JS
SUSAP KISOK7FR23	R	040		M	CA		2302	+	00370			A	JS
SUSAP KISOK7FR23	R	050UHIROK7EA0EY		DF				+	02100			A	JS
SUSAP KISOK7FR23	R	060UHIROK7EA0EE	R	HM			05000050	+	02100			A	JS

[illegible][illegible]

CITY AND STATE KINSTON, NC	ELEVATION: 93 THRE: 86 AIRPORT NAME: KINSTON RGNL JETPORT AT STALLINGS FLD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 23, AMDT 3 29 MAY 2014	SUP:
				AMDT: 2
				DATED: 10/25/2007

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	WINTI	WINTI	010	IAF	HF	R	FO		230.2(221.2T)	005.0	AA 02500	
		WINTI	010	FACF	IF		FB				AA 02500	
		HUKOR	020	FAF	TF		FB	0.5	230.2(221.2T)	007.0	AA 01700	
		WOVTA	021	SDF	TF		FB	0.3	230.2(221.2T)	002.3	AA 00920 GS 00964	
		RW23	030	MAP	TF		FO	0.3	230.2(221.2T)	002.6	AT 00136	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		230.2(221.2T)		AA 00370	
	UHIRO	050		DF		FO				AA 02100	
	UHIRO	060		HM	R	FO		050.0(041.0T)	005.0	AA 02100	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HUKOR	N352418.32	W0773149.14	N3524.305	W07731.819
	UHIRO	N351100.30	W0774557.75	N3511.005	W07745.963
	WINTI	N352936.29	W0772609.25	N3529.605	W07726.154
	WOVTA	N352233.71	W0773340.73	N3522.562	W07733.679
	RW23	N352036.01	W0773546.16	N3520.600	W07735.769

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW23	00086	50

QUALITY
CHECKED

CITY AND STATE KINSTON, NC	ELEVATION: 93	THRE: 86	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 23, AMDT 3 29 MAY 2014	SUP:
	AIRPORT NAME: KINSTON RGNL JETPORT AT STALLINGS				AMDT: 2
	FLD				DATED: 10/25/2007