

**FLIGHT STANDARDS SERVICE
NDB STANDARD INSTRUMENT APPROACH PROCEDURE**

TITLE 14 CFR PART 97.27

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

If an instrument approach procedure of the above type is conducted at the below named airport, it shall be conducted in accordance with a charted instrument approach procedure predicted on the specifications contained herein, unless an approach is conducted in accordance with a different procedure for such airport authorized by the Administrator. Minimum altitudes shall correspond with those established for enroute operations in the particular area or as set forth below.

<u>AIRPORT</u> GORDON MUNI	<u>AIRPORT ID</u> KGRN	<u>PROCEDURE NAME</u> NDB RWY 22	<u>ORIGINAL/AMENDMENT</u> 4C	<u>CITY</u> GORDON	<u>STATE</u> NE
<u>AIRPORT ELEVATION</u> 3562	<u>TDZE</u> 3562	<u>SUPERSEDED</u> NDB RWY 22	<u>ORIGINAL/AMENDMENT</u> 4B	<u>DATED</u> 04/27/2017	<u>MAG VAR</u> 9E
<u>FACILITY</u> GRN	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 19 JULY 2018	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL SUSPEND</u>	<u>EPOCH YEAR</u> 2000

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
TST VOR/DME		GRN NDB					060.45	52.20	6200
EVENN INT		GRN NDB					001.90	40.13	6000

MISSED APPROACH

MAP:

GRN NDB

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 5400 THEN RIGHT TURN DIRECT GRN NDB AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

- 1. PT R **SIDE OF COURSE** 035.71 **OUTBOUND** 5300 **FT WITHIN** 10 **MILES OF** GRN NDB (IAF)
- 2.
- 3. **FAC:** 215.71 **FAF:** **DIST FAF TO MAP:** **DIST FAF TO THLD:**
- 4. **MIN ALT:**
- 8. **MSA FROM:** GRN NDB 5600

EQUIPMENT REQUIREMENTS NOTES:

NOTES:

CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART NOTE: CIRCLING RWY 11, 29 NA AT NIGHT.

ADDITIONAL FLIGHT DATA:



FAS OBST: 3989 AAO 425234N/1020331W.
FAC CROSSES RWY C/L EXTENDED 3000 FT FROM THLD.
HOLD NE, RT, 215.71 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA STANDARD - CAT A, B 900-2

CATEGORY:	A			B			C			D			E			
	FINAL TYPE	DA/MDA	VIS	HAT/HAA												
S-22	4420	1	858	4420	1 1/4	858		NA			NA					
CIRCLING	4420	1 1/4	858	4420	1 1/4	858		NA			NA					

CHANGES - REASONS

1. LINES OF MINIMA CATS C AND D MADE 'NA' - AIRPORT REQUEST AND RAPT CONCURRENCE.

PDF EDITS:

-5, TERMINAL ROUTES, DELETED '/21.00 DME' AFTER 'EVENN INT'
-5, PROFILE LINE 1, ADDED 'NDB' IN 'MILES OF: GRN NDB (IAF)'

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA OTHER: ZDV, AMGR

FLIGHT CHECKED BY

FLIGHT INSPECTION REVIEW NOT REQUIRED - PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-333) MEMO, DEC 22, 2017.

DEVELOPED BY

LUCAS MCCLLOUD

Digitally signed by
LUCAS MCCLLOUD
Feb 28, 2018

APPROVED BY

JULIE MORGAN

OFFICE *Digitally signed by* **DATE**

ROBERT G HAMILTON

Mar 02, 2018

OFFICE **DATE**
AJV-5422 01/31/2018

OFFICE *Digitally signed by* **DATE**

AJV-5420 **ROBERT G HAMILTON**

Mar 02, 2018

TITLE
MANAGER

