

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE												
ODF VORTAC (IAF)	LIBIC (NOPT) (FB)	210.68 / 5.51	4000	LPV: DA LNAV/VNAV: DA LNAV: RW24											
LIBIC (IF/IAF)	KECEB (FB)	242.09 / 6.66	3200												
KECEB (FAF)	RW24 (MAP) (FO)	242.02 / 5.34		CLIMB TO 4000 DIRECT EYUBU AND HOLD.											
RW24 (MAP)	1848 MSL	242.02													
1848 MSL	EYUBU (FO)		4000	ADDITIONAL FLIGHT DATA: HOLD SW, RT, 061.85 INBOUND. CHART FAS OBST: 1799 TREE 343040N/0833052W DISTANCE TO THLD FROM 404 HATH: 1.10 NM. WAAS CHANNEL # 49121 REFERENCE PATH ID: W24A LTP HAE: 411.3 M											
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NE LIBIC, RT, 242.09 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>242.02</u> FAF: <u>KECEB</u> DIST FAF TO MAP: <u>5.34</u> THLD: <u>5.34</u> 4. MIN. ALT: <u>LIBIC 4000, KECEB 3200</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>3200</u> GS ALT AT: <u>KECEB 3200</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>53.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u>RW24 6000</u>															
				MAG VAR: 5W EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1851	1 3/8	404	1851	1 3/8	404	1851	1 3/8	404	1851	1 3/8	404			
LNAV/VNAV DA	2153	2 1/2	706	2153	2 1/2	706	2153	2 1/2	706	2153	2 1/2	706			
LNAV MDA	2060	1	613	2060	1	613	2060	1 3/4	613	2060	1 3/4	613			
CIRCLING	2060	1	612	2100	1	652	2100	1 3/4	652	2240	2 1/2	792			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON ODF VORTAC AIRWAY RADIALS 222 CW 258. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 1448 THRE: 1447		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
CORNELIA, GA		AIRPORT NAME:		HABERSHAM COUNTY		RNAV (GPS) RWY 24, AMDT 1				AMDT: ORIG					
						30 JUN 2011				DATED		06/08/2006			

QUALITY
2
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE GAINESVILLE ALTIMETER SETTING AND INCREASE ALL DA 69 FEET AND ALL MDA 80 FEET: INCREASE VISIBILITY LPV AND LNAV/VNAV ALL CATS 1/4 MILE, LNAV CAT C AND D 1/4 MILE, CIRCLING CAT C AND D 1/4 MILE.

CHART NOTE: WHEN VGSI INOP, STRAIGHT - IN / CIRCLING RWY 24 PROCEDURE NA AT NIGHT.

CHART NOTE: BARO-VNAV NA WHEN USING GAINESVILLE ALTIMETER SETTING.

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 34C (93F).

QUALITY
2
CHECKED

CITY AND STATE CORNELIA, GA	ELEVATION: 1448 AIRPORT NAME: HABERSHAM COUNTY	THRE: 1447	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 24, AMDT 1 30 JUN 2011	SUP:
					AMDT: ORIG
					DATED: 06/08/2006

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAJR
RUNWAY	RW24
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W24A
LTP/FTP LATITUDE	343014.2960N
LTP/FTP LONGITUDE	0833256.4320W
LTP/FTP ELLIPSOIDAL HEIGHT	+04113
FPAP LATITUDE	342925.6400N
FPAP LONGITUDE	0833426.8000W
THRESHOLD CROSSING HEIGHT (TCH)	00053.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

6CAC726A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+04411
FPAP ORTHOMETRIC HEIGHT	+04411



CITY AND STATE
CORNELIA, GA

ELEVATION: 1448 THRE: 1447
AIRPORT NAME:
HABERSHAM COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 24, AMDT 1
30 JUN 2011

SUP:
AMDT: ORIG
DATED: 06/08/2006

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	ORIG
DATED:	06/08/2006

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KAJRK7PR24	RW24	001	0000W24A0N3430142960W08332564320+041130300N3429256400W08334268000106751072000530F4005006CAC726A									
	SUSAP KAJRK7PR24	RW24	002E	+04411+04411LPV	49121								

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KAJRK7SRW24	K7PG		0	18018006025							M	

CITY AND STATE
CORNELIA, GA

ELEVATION: 1448 THRE: 1447
AIRPORT NAME:
HABERSHAM COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 24, AMDT 1
30 JUN 2011

SUP:
AMDT: ORIG
DATED: 06/08/2006