

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: RIW VOR/DME						
RIW VOR/DME ROWEY INT/RIW 30.98 DME (IAF) SASSY INT/RIW 16.39 DME (IF)		PYLOT INT/6.50 DME			281.01 / 6.50			7900		CLIMB TO 7900 IN RIW VOR/DME HOLDING PATTERN. ADDITIONAL FLIGHT DATA: HOLD W, RT, 101.01 INBOUND. CHART FAS OBST: 5682 ANT 430448N/1082922W 5920 AAO 430715N/1083703W. PYLOT TO RW10: 3.00/50. CHART CIRCLING ICON. FINAL END POINT (CFCJH) AT 430413N/1082820W (DO NOT CHART) FAC 154 FT L OF RWY C/L EXTENDED 3000 FT FROM THLD.						
		SASSY INT/RIW 16.39 DME (NOPT)			146.00 / 6.61 & 100.63 / 9.59 (RIW R-281)			8800								
		PYLOT INT/6.50 DME			101.01 / 9.89 (RIW R-281)			7400								
1. PT <u> R </u> SIDE OF COURSE <u> 281.01 </u> OUTBOUND <u> 7800 </u> FT WITHIN <u> 10 </u> MILES OF <u> PYLOT </u> (IAF) 2. _____ 3. FAC <u> 101.01 </u> FAF <u> PYLOT INT/6.50 DME </u> DIST FAF TO MAP _____ THLD <u> 5.72 </u> 4. MIN. ALT <u> PYLOT 7400, WUNIB/RIW 2.20 DME 6000* </u> 8. MSA FROM: <u> RIW VOR/DME 076-166 8700, 166-256 11900, 256-076 9700 </u>										MAG VAR: 10E		EPOCH YEAR: 2020				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-10	6000	1	484	6000	1	484	6000	1 3/8	484	6000	1 3/8	484				
CIRCLING	6000	1	484	6000	1	484	6000	1 1/2	484	6120	2	604				
WUNIB FIX MINIMUM (DME REQUIRED)																
S-10	5940	1	424	5940	1	424	5940	1 1/4	424	5940	1 1/4	424				
CIRCLING	6000	1	484	6000	1	484	6000	1 1/2	484	6120	2	604				
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LANDER ALTIMETER SETTING AND INCREASE ALL @ NA WHEN LOCAL WEATHER NOT AVAILABLE. MDA 60FT AND INCREASE S-10 CAT C AND D VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/8 MILE, INCREASE WUNIB FIX MINIMUMS CAT C AND D VISIBILITY 1/8 MILE. CHART NOTE: RWY 10 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. *6060 WHEN USING LANDER ALTIMETER SETTING.																
CITY AND STATE RIVERTON, WY		ELEVATION: 5516 AIRPORT NAME: RIVERTON RGNL		TDZE: 5516		FACILITY IDENTIFIER: RIW		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 10, AMDT 10B 12 OCTOBER 2017				SUP				
												AMDT 10A				
												DATE 07/21/2016				

