

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>Arrival Name</u>	<u>Number</u>	<u>STAR Computer Code</u>	<u>Superseded Number</u>	<u>Dated</u>	<u>Effective Date</u>
WITTI (RNAV)	FOUR	WITTI.WITTI4	THREE	06/22/2017	01 FEB 2018

TRANSITION ROUTES:

Transition Name	Transition Computer Code	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	MAA	Crossing Altitude/Fixes
JOHNSTONE POINT	JOH.WITTI4	JOH VOR/DME	JOH VOR/DME						
			WITTI	272.65	50.84	16000	5200		AT/ABOVE 16000
MIDDLETON ISLAND	MDO.WITTI4	MDO VOR/DME	MDO VOR/DME						AT/ABOVE FL260
			WITTI	309.30	97.51	16000	5100		AT/ABOVE 16000
REMBY	REMBY.WITTI4	REMBY	REMBY						AT/ABOVE FL260
			WITTI	258.87	66.05	16000	5800		AT/ABOVE 16000
TIEKL	TIEKL.WITTI4	TIEKL	TIEKL						AT/ABOVE FL260
			OWXUP	237.56	72.40	16000	9800		
			WITTI	217.49	29.19	16000	6700		AT/ABOVE 16000
TMSON	TMSON.WITTI4	TMSON	TMSON						AT/ABOVE FL260
			WITTI	244.06	92.79	16000	9100		AT/ABOVE 16000

ARRIVAL ROUTE DESCRIPTION:

LANDING RWY 07R/L: FROM WITTI ON TRACK 271.08/30.21 TO CROSS GAYLL BETWEEN 12000 AND 15000, THEN ON TRACK 277.51/17.02 TO CROSS SLOOW AT OR ABOVE 8000, THEN ON TRACK 304.87/8.43 TO CROSS SILTY AT OR ABOVE 5400, THEN ON TRACK 252.74/10.74 TO CROSS ANDDI AT 5000 AND AT 210 KIAS, THEN ON TRACK 252.74. EXPECT RADAR VECTORS TO FINAL APPROACH COURSE.

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED AFTER GAYLL.
NOTE: RNAV 1
NOTE: GPS REQUIRED



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>Arrival Name</u>	<u>Number</u>	<u>STAR Computer Code</u>	<u>Superseded Number</u>	<u>Dated</u>	<u>Effective Date</u>
WITTI (RNAV)	FOUR	WITTI.WITTI4	THREE	06/22/2017	01 FEB 2018

NOTE: TURBOJET AIRCRAFT ONLY
NOTE: EXPECT RUNWAY ASSIGNMENT FROM ANCHORAGE APPROACH ON INITIAL CONTACT.

FIXES AND/OR HOLDING PATTERNS:

CHART HOLDING AT GAYLL: HOLD E, RT, 271.08 INBOUND, 10 NM LEGS.

COMMUNICATIONS:

ANCHORAGE APP CON, ATIS.

AIRPORTS SERVED:

AIRPORT NAME

CITY

STATE

TED STEVENS ANCHORAGE INTL

ANCHORAGE

AK

LOST COMMUNICATIONS PREFERENCES:

AFTER ANDDI, TURN RIGHT HEADING 021 DEGREES, INTERCEPT THE RWY 7R OR RWY 7L LOCALIZER, MAINTAIN 3000, PROCEED ON ILS OR LOC/DME RWY 7R APPROACH OR ILS OR LOC/DME RWY 7L APPROACH.

REMARKS:

THIS AMENDMENT DOES NOT QUALIFY AS A PERIODIC REVIEW.

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: NOT CONDUCTED
REFERENCE MAGNETIC VARIATION = PANC 16E/2020.
CHART: LOST COMM TRACK FROM ANDDI.
CHART LOCALIZERS: I-ANC, I-TGN.
CHART: NCA 20.
CHART: NCA 13.
DO NOT CHART MOCAs.

FLIGHT INSPECTED BY:

ORGANIZATION:

DATE:

FLIGHT INSPECTION NOT REQUIRED, ROBERT STUCKERT, MANAGER

AJW-331

07/31/2015

Digitally signed by
Flight Inspected Signature: **VICTOR B NASO**
Nov 21, 2017

DEVELOPED BY Digitally signed by

BRYAN BLUE **BRYAN W BLUE**
Oct 25, 2017

AJV-5411

08/15/17

Developed By Signature:

APPROVED BY:

GEORGE DAVIS

Digitally signed by
CASIMIR L TABAKA
Nov 21, 2017

AJV-5410

Approved By Signature:

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>Arrival Name</u>	<u>Number</u>	<u>STAR Computer Code</u>	<u>Superseded Number</u>	<u>Dated</u>	<u>Effective Date</u>
WITTI (RNAV)	FOUR	WITTI.WITTI4	THREE	06/22/2017	01 FEB 2018

CHANGES:

1. CHANGED AIRPORT MAGVAR FROM 18E/2020 TO 16E/2020.
2. CHANGED ALL HEADINGS, COURSES, AND TRACKS +2 DEGREES.
3. CHANGED RECOMMENDED NAVAID FROM JOH TO AKN.

REASONS:

1. AIRPORT CAT II/III MAGVAR UPDATE INITIATIVE EFFECTIVE 02/01/2018
2. AIRPORT MAGVAR UPDATED FROM 18E/2020 TO 16E/2020
3. TO MAINTAIN SAME MAGVAR AS AIRPORT.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STAR (DATA RECORD)**

Arrival Name		Number		STAR Computer Code		Superseded Number		Dated		Effective Date	
WITTI (RNAV)		FOUR		WITTI.WITTI4		THREE		06/22/2017		01 FEB 2018	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
En Route Transition											
JOH VOR/DME	602851.43N / 1463557.61W	Y		IF					JOH.WITTI4		
WITTI	604428.26N / 1481405.82W	Y	FB	TF	288.65	50.84	AT/ABOVE 16000				
En Route Transition											
MDO VOR/DME	592518.50N / 1462100.05W	Y		IF			AT/ABOVE FL260		MDO.WITTI4		
WITTI	604428.26N / 1481405.82W	Y	FB	TF	325.30	97.51	AT/ABOVE 16000				
En Route Transition											
REMBY	604000.00N / 1460000.00W	Y		IF			AT/ABOVE FL260		REMBY.WITTI4		
WITTI	604428.26N / 1481405.82W	Y	FB	TF	274.87	66.05	AT/ABOVE 16000				
En Route Transition											
TIEKL	612337.55N / 1450330.59W	Y		IF			AT/ABOVE FL260		TIEKL.WITT4		
OWXUP	610156.06N / 1472617.63W	Y	FB	TF	253.56	72.40					
WITTI	604428.26N / 1481405.82W	Y	FB	TF	233.49	29.19	AT/ABOVE 16000				
En Route Transition											
TMSON	610236.58N / 1450750.63W	Y		IF			AT/ABOVE FL260		TMSON.WITT4		

QUALITY

14

CHECKED

FAA Form 8260-17.2 (06/15)

Electronic Version

Page 1 of 2

QUALITY
14
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STAR (DATA RECORD)**

Arrival Name					Number		STAR Computer Code		Superseded Number		Dated	Effective Date
WITTI (RNAV)					FOUR		WITTI.WITTI4		THREE		06/22/2017	01 FEB 2018
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS		
WITTI	604428.26N / 1481405.82W	Y	FB	TF	260.06	92.79	AT/ABOVE 16000					
Runway Transition												
WITTI	604428.26N / 1481405.82W	Y		IF			AT/ABOVE 16000					
GAYLL	605306.14N / 1491311.20W	Y	FB	TF	287.08	30.21	12000B/15000					
SLOOW	605948.56N / 1494513.95W	Y	FB	TF	293.51	17.02	AT/ABOVE 8000					
SILTY	610619.40N / 1495611.64W	Y	FB	TF	320.87	08.43	AT/ABOVE 5400					
ANDDI	610603.44N / 1501818.79W	Y	FO	TF	268.74	10.74	AT 5000	AT 210K				
PANC:RWY 07L, RWY 07R				FM	268.74				RECOMMENDED NAVAID: AKN VORTAC			

