

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE
GASTO	CEYAB (TF) (FB) (RNP 2.00)	042.80 / 16.77	2000
IVANN	ECIKI (TF) (FB) (RNP 2.00)	164.52 / 7.77	3600
ECIKI (IAF)	NAJIL (TF) (FB) (RNP 1.00)	117.00 / 7.52	2000
CEYAB (IAF)	NAJIL (TF) (FB) (RNP 1.00)	028.57 / 6.88	2000
NAJIL (IF)	WEBBI (TF) (RNP 1.00)	073.55 / 6.53	1600
(SEE FORM 8260-10)			

LPV: DA  
LNAV/VNAV: DA  
LNAV: RW07L

CLIMB TO 800 THEN CLIMBING RIGHT TURN TO 2500 DIRECT JUKEP AND HOLD.

ADDITIONAL FLIGHT DATA:  
HOLD NE, RT, 210.00 INBOUND.  
CHART FAS OBST: 343 TREE 610936N/1500201W.  
DISTANCE TO THLD FROM 200 HAT: 0.46 NM.  
CHART VDP AT 1.22 NM TO RW07L\*  
\*LNAV ONLY.  
WAAS CHANNEL # 86215  
REFERENCE PATH ID: W07B  
354 AAO 610915N/1501018W  
LTP HAE: 45 M

MAG VAR: 16E      EPOCH YEAR: 2020

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. PROFILE STARTS AT NAJIL
3. FAC: 073.75 FAF: WEBBI DIST FAF TO MAP: 4.46 THLD: 4.46
4. MIN. ALT: NAJIL 2000, WEBBI 1600
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT: 1600 GS ALT AT: WEBBI 1600 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 53.5 34:1 IS CLEAR
8. MSA FROM: RW07L 8900

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	328	1800	200	328	1800	200	328	1800	200	328	1800	200			
LNAV/VNAV DA	601	6000	473	601	6000	473	601	6000	473	601	6000	473			
LNAV MDA	600	2400	472	600	2400	472	600	5000	472	600	5000	472			
CIRCLING	700	1	549	700	1	549	700	1 1/2	549	800	2	649			

NOTES:  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -24C (-12F) OR ABOVE 42C (107F).  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT IVANN ON V440 WESTBOUND AND ARRIVALS AT GASTO ON V462 SOUTHWEST BOUND.  
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).



CITY AND STATE <b>ANCHORAGE, AK</b>	ELEVATION: 151      TDZE: 128 AIRPORT NAME: <b>TED STEVENS ANCHORAGE INTL</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 7L, AMDT 2D 1 FEBRUARY 2018</b>	SUP: AMDT: <b>2C</b> DATED <b>10/15/2015</b>
--	---	-------------------------------------	---	--

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
WEBBI (FAF)	RW07L (MAP) (TF) (FO) (RNP 0.30)	073.75 / 4.46	
RW07L (MAP)	800 MSL (CA)	073.75	800
800 MSL	JUKEP (DF) (FO) (RNP 1.00)		2500



CITY AND STATE <b>ANCHORAGE, AK</b>	ELEVATION: 151      TDZE: 128 AIRPORT NAME: <b>TED STEVENS ANCHORAGE INTL</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 7L, AMDT 2D</b> 1 FEBRUARY 2018	SUP:
				AMDT: <b>2C</b>
				DATED: <b>10/15/2015</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PANC
RUNWAY	RW07L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07B
LTP/FTP LATITUDE	611011.1535N
LTP/FTP LONGITUDE	1500029.9995W
LTP/FTP ELLIPSOIDAL HEIGHT	+00450
FPAP LATITUDE	611011.3200N
FPAP LONGITUDE	1495653.8800W
THRESHOLD CROSSING HEIGHT (TCH)	00053.5
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER CA966DE2

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+00389
FPAP ORTHOMETRIC HEIGHT	+00389



CITY AND STATE <b>ANCHORAGE, AK</b>	ELEVATION: 151      TDZE: 128 AIRPORT NAME: <b>TED STEVENS ANCHORAGE INTL</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 7L, AMDT 2D</b> 1 FEBRUARY 2018	SUP:
				AMDT: <b>2C</b>
				DATED: <b>10/15/2015</b>