

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW07R CLIMB TO 900 THEN CLIMBING RIGHT TURN TO 3000 DIRECT JUKEP AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 210.00 INBOUND. CHART FAS OBST: 356 POLE 610933N/1500202W. DISTANCE TO THLD FROM 200 HAT: 0.46 NM. CHART VDP AT 1.38 NM TO RW07R* *LNAV ONLY. WAAS CHANNEL # 81815 REFERENCE PATH ID: W07A LTP HAE: 46.1 M								
GASTO	CEYAB (TF) (FB) (RNP 2.00)	042.80 / 16.77	2000									
IVANN	ECIKI (TF) (FB) (RNP 2.00)	164.52 / 7.77	3600									
CEYAB (IAF)	WEWWO (TF) (FB) (RNP 1.00)	028.38 / 6.70	2000									
ECIKI (IAF)	WEWWO (TF) (FB) (RNP 1.00)	118.41 / 7.50	2000									
WEWWO (IF)	TULLI (TF) (FB) (RNP 1.00)	073.55 / 5.70	1600									
(SEE FORM 8260-10)												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT WEWWO 3. FAC: 073.72 FAF: TULLI DIST FAF TO MAP: 4.44 THLD: 4.44 4. MIN. ALT: WEWWO 2000, TULLI 1600 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1600 GS ALT AT: TULLI 1600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 54.8 34:1 IS CLEAR 8. MSA FROM: RW07R 8800												
				MAG VAR: 16E EPOCH YEAR: 2020								
MINIMUMS												
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A								
CATEGORY =====>				STANDARD								
	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	332	1800	200	332	1800	200	332	1800	200	332	1800	200
LNAV/VNAV DA	660	1 3/8	528	660	1 3/8	528	660	1 3/8	528	660	1 3/8	528
LNAV MDA	640	2400	508	640	2400	508	640	5500	508	640	5500	508
CIRCLING	740	1	589	740	1	589	740	1 1/2	589	800	2	649
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -24C (-11F) OR ABOVE 43C (109F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT IVANN ON V440 WESTBOUND AND ARRIVALS AT GASTO ON V462 SOUTHWEST BOUND. (CONTINUED ON PAGE 2)												
CITY AND STATE		ELEVATION: 151 TDZE: 132		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
ANCHORAGE, AK		AIRPORT NAME:				RNAV (GPS) Y RWY 7R, AMDT 4D			AMDT: 4C			
		TED STEVENS ANCHORAGE INTL				1 FEBRUARY 2018			DATED 10/15/2015			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
TULLI (FAF)	RW07R (MAP) (TF) (FO) (RNP 0.30)	073.72 / 4.44	
RW07R (MAP)	900 MSL (CA)	073.72	900
900 MSL	JUKEP (DF) (FO) (RNP 1.00)		3000

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/4 SM, AND LNAV CAT C AND D VISIBILITY TO 1 3/8 SM.

**QUALITY
20
CHECKED**

CITY AND STATE ANCHORAGE, AK	ELEVATION: 151	TDZE: 132	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 7R, AMDT 4D 1 FEBRUARY 2018	SUP:
	AIRPORT NAME:				AMDT: 4C
	TED STEVENS ANCHORAGE INTL				DATED: 10/15/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PANC
RUNWAY	RW07R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	611004.1215N
LTP/FTP LONGITUDE	1500234.3365W
LTP/FTP ELLIPSOIDAL HEIGHT	+00461
FPAP LATITUDE	611004.3720N
FPAP LONGITUDE	1495821.5350W
THRESHOLD CROSSING HEIGHT (TCH)	00054.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	107.00
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

4FD27ED7

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+00401
FPAP ORTHOMETRIC HEIGHT	+00401

QUALITY
20
CHECKED

CITY AND STATE

ANCHORAGE, AK

ELEVATION: 151

TDZE: 132

AIRPORT NAME:

TED STEVENS ANCHORAGE INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Y RWY 7R, AMDT 4D

1 FEBRUARY 2018

SUP:

AMDT: 4C

DATED: 10/15/2015