

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES											MISSED APPROACH				
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW35 CLIMB TO 3400 DIRECT FINEB AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 173.07 INBOUND. CHART FAS OBST: 1294 TREE 385155N/0971325W DISTANCE TO THLD FROM 317 HAT: 0.86 NM. CHART VDP AT 1.35 NM TO RW35* *LNAV ONLY. WAAS CHANNEL # 97734 REFERENCE PATH ID: W35A CHART CIRCLING ICON. LTP HAE: 321.7 M					
ECHEL (IAF)		ADELA (NOPT) (TF) (FB) (RNP 1.00)			053.01 / 5.00			3400							
EZXIX (IAF)		ADELA (NOPT) (TF) (FB) (RNP 1.00)			293.13 / 5.00			3400							
ADELA (IF/IAF)		IKEHU (TF) (FB) (RNP 1.00)			353.07 / 5.65			2900							
IKEHU (FAF)		ZEDUD/2.00 NM TO RW35 (TF) (FB) (RNP 0.30)			353.07 / 3.35										
ZEDUD/2.00 NM TO RW35 (SEE FORM 8260-10)		RW35 (MAP) (TF) (FO) (RNP 0.30)			353.07 / 2.00										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S ADELA, RT, 353.07 INBOUND, 3400 FT. IN LIEU OF PT (IAF) 3. FAC: 353.07 FAF: IKEHU DIST FAF TO MAP: 5.35 THLD: 5.35 4. MIN. ALT: ADELA 3400, IKEHU 2900, ZEDUD/2.00 NM TO RW35 1820* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2900 GS ALT AT: IKEHU 2900 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR 8. MSA FROM: _____											MAG VAR: 7E		EPOCH YEAR: 1985		
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1468	1	317	1468	1	317	1468	1	317		NA				
LNAV/VNAV DA	1468	1	317	1468	1	317	1468	1	317		NA				
LNAV MDA	1620	1	469	1620	1	469	1620	1 3/8	469		NA				
CIRCLING	1740	1	587	1740	1	587	1980	2 1/2	827		NA				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 17C (2F) OR ABOVE 54C (130F). @ CAT C 900-2 1/2 CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). *LNAV ONLY (CONTINUED ON PAGE 2)															
CITY AND STATE ABILENE, KS		ELEVATION: 1153 TDZE: 1151 AIRPORT NAME: ABILENE MUNI			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1B 17 AUGUST 2017					SUP: AMDT: 1A DATED 07/24/2014			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW35 (MAP)	1468 MSL (CA)	353.07	
1468 MSL	FINEB (DF) (FO) (RNP 1.00)		3400

NOTES, (CONT.):

CHART NOTE: BARO-VNAV AND VDP NA WHEN USING SALINA ALTIMETER SETTING.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SALINA ALTIMETER SETTING.

CHART NOTE: CIRCLING RWY 17 NA AT NIGHT.

TAA

	FROM	TO	ALT
1.	293/30 CW 053/30 (NOPT)	ADELA (IF/IAF) (FB)	3400
2.	053/30 CW 173/30	ECHEL (IAF) (FB)	3400
3.	173/30 CW 293/30	EZTIX (IAF) (FB)	3400

QUALITY
29
CHECKED

CITY AND STATE
ABILENE, KS

ELEVATION: 1153 TDZE: 1151
AIRPORT NAME:
ABILENE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 35, AMDT 1B
17 AUGUST 2017

SUP:
AMDT: 1A
DATED: 07/24/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	K78
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	385354.3315N
LTP/FTP LONGITUDE	0971409.1020W
LTP/FTP ELLIPSOIDAL HEIGHT	+03217
FPAP LATITUDE	385523.5100N
FPAP LONGITUDE	0971408.9600W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1504
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

2E4B9CD2

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+03505
FPAP ORTHOMETRIC HEIGHT	+03505

QUALITY
29
CHECKED

CITY AND STATE

ABILENE, KS

ELEVATION: 1153

TDZE: 1151

AIRPORT NAME:

ABILENE MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1B

17 AUGUST 2017

SUP:

AMDT: 1A

DATED: 07/24/2014